LIST OF ABBREVIATIONS

LIST	OF ABBREVI	<u>A TI O</u>	N S
	ABOVE	JC	JANITOR CLOSET
	ABOVE FINISHED FLOOR ACCESS	JT JB	JOINT JUNCTION BOX
AD	ACCESS DOOR	KO	KNOCK OUT
AP ACT	ACCESS PANEL ACOUSTICAL TILE	KO	KNOCK OUT
	ADDENDUM	LAM	LAMINATE
	ADJACENT or ADJUSTABLE	LAW	LAVATORY
	AGGREGATE AIR CONDITIONER		LEFT HAND
	ALUMINUM	LKR L.P.	LOCKER LOW POINT
	AMERICAN CONCRETE INSTITUTE AMERICANS W/ DISABILITIES ACT	L.I .	2011101111
ASTM	AMERICAN SOCIETY FOR TESTING	MH MFR	MANHOLE MANUFACTURE(R)
	MATERIALS AMERICAN WIRE GAGE	MAS	MASONRY
	APPROXIMATE		MASONRY OPENING MATCH EXISTING
BB	BASEBOARD		MATERIAL
BP	BASE PLATE	MAX	MAXIMUM
	BEAM	MECH MC	MECHANIC (AL) MEDICINE CABINET
	BEARING BENCH MARK	MBR	MEMBER
	BETWEEN	MTL MN	METAL MINIMUM
BLK BLKG	BLOCKING	MR	MIRROR
BD	BOARD	MISC MC	MISCELLANEOUS MISCELLANEOUS CHANNEL
B.O.	BOTTOM OF		MOUNTED CHANNEL
САВ	CABINET		MOVABLE MULLION
C.I. C.H.	CAST IRON CEILING HEIGHT	MUL	IVIOLLIOIN
СВ	CATCH BASIN	NFPA	NATIONAL FIRE PROTECTION ASSOCIATION
CLG CEM	CEILING CEMENT	NRC	NOSE REDUCTION COEFFICIENT
CL	CENTER LINE	NOM	NOMINAL NOT IN CONTRACT
CT CO	CERAMIC TILE CLEAN OUT	n.i.c. nts	NOT TO SCALE
CLR	CLEAR(ANCE)	ОС	ON CENTER
CW	COLD WATER COLUMN	OPNG	OPENING OPPOSITE
CONC	CONCRETE	OPP OPH	OPPOSITE OPPOSITE HAND
CMU CONT	CONCRETE MASONRY UNIT CONTINUOUS or CONTINUE	OD	OUTSIDE DIAMETER
CONV	CONVECTOR	OZ OA	OUNCE OVERALL
CG	CORNER GUARD	ОН	OVERHEAD
DP DEG	DAMPROOFING DEGREE	PNT/PT/D/	PAINT(ED)
DTL DIAG	DETAIL DIAGONAL	PR	PAIR
DFF	DIFFUSER	PNL PTN	PANEL PARTITION
DM DISP	DIMENSION DISPENSER	PLAS	PLASTER
DBL	DOUBLE	PLAM PL	PLASTIC LAMINATE PLATE
DN DWG	DOWN DRAWING	PLWD	PLYWOOD
DF	DRINK FOUNTAIN	PVC PSF	POLYVINYL CHLORIDE or COATIN POUNDS PER SQUARE FOOT
EA	EACH	PSI	POUNDS PER SQUARE INCH
ELEC EP	ELECTRICAL or ELECTRIC ELECTRIC PANEL	-	TYQUANTITY
E.W.C	ELECTRIC WATER COOLER	QT	QUARRY TILE
ELEV	ELEVATION ELEVATOR	RAD REF	RADIUS or RADIATOR REFERENCE
EMER	EMERGENCY	REINF	REINFORCEMENT
EQ EQUP	EQUAL EQUIPMENT	reqd ret	required Return
EXH	EXHAUST	RD	ROOF DRAIN
EXIST	EXISTING ERESH AIR INTAKE	RO	ROUGH OPENING
F.A.I. F.O.	FRESH AIR INTAKE FACE OF	SAD SAN	SADDLE SANITARY
F.BR.	FACE OF BRICK	SCHED	SCHEDULE
F.O.C F.O.M	FACE OF CONCRETE FACE OF MASONRY	SECT	SECTION
F.O.S	FACE OF STUDS	SIM STC	SIMILAR SOUND TRANSMISSION
FIN FA	FINISH FIRE ALARM		COEFFICIENT
FAA	FIRE ALARM ANNUNCIATOR	SPKR SPEC	SPEAKER SPECIFICATION
FHVC F.D.	FIRE HOSE VALVE CABINET FLOOR DRAIN OF FIRE DAMPER	SF	SQUARE FOOT . STAINLESS STEEL
FE	FIRE EXTINGUISHER	SD	STORM DRAIN
FP	FIRE PROOF	S.F.T. SW	STRUCTURAL FACED TILE SWITCH
FLUOR FT	FLUORESCENT FOOT or FEET		
FTG	FOOTING	TEL TV	TELEPHONE TELEVISION
FDN F.A.I.	FOUNDATION FRESH AIR INTAKE	TEMP	TEMPERED
FLR	FLOOR	TERR THK	TERRAZZO THICK
GALV	GAUGE	T.O.	TOP OF
GALV GEN	GALVANIZED GENERAL	TYP	TYPICAL
GL	GLASS OF GLAZING	U.L.	UNDERWRITERS LABORATORY
GB GND	GRAB BAR	UC UNEX	UNDERCUT UNEXCAVATED
GND GYP	GROUND GYPSUM	U.C.C.	UNIFORM CONSTRUCTION CODE
GWB/	GYPSUM WALL BOARD	U.O.N.	UNLESS OTHERWISE NOTED
GYP.BD HC	HANDICAPPED	V.I.F.	VERIFY IN FIELD
HR HDWR	HAND RAIL HARDWARE	VCT VWC	VINYL COMPOSITION TILE VINYL WALL COVERING
HWD	HARDWOOD	VB	VINYL BASE
HVAC	HEATING VENTILATING AIR CONDITIONING	VOL	VOLUME
	HEIGHT	WC	WATER CLOSET
НМ	HOLLOW METAL HOSE BIBB	WD WH	WOOD WATER HEATER
H.P.	HIGH POINT	WP	WATER PROOF
INCAND	INCANDESCENT	WWF WT	WELDED WIRE MESH WEIGHT
INCL	INCLUDE(D), (ING)	WO	WINDOW OPENING
INSUL	INTERIOR DIAMETER INSULATE(D), (ING), (TION)	W/ W/O	WITH WITH OUT
		, , <i>, ,</i> \smile	771111 001

WITH OUT

WIRE GLASS

INVERT

INV EL INVERT ELEVATION

SYMBOL KEY

AREA SECTIONED

REVISION

NUMBER/LETTER AND

"CLOUDED" AREA REVISED

DELTA SYMBOL

NUMBER

AREA DETAILED

DETAILED -

SHEET NUMBERING A-XXX

DETAIL SECTION DETAIL REFERENCE REFERENCE

SHEET NO. IN CHAPTER

CHAPTER LETTER

NEW SINGLE FAMILY RESIDENCE: 1A PLUNKETT PL WESTPORT, CT 06880



ELEVATION POINT

X PARTITION TYPE SYMBOL & LETTER

(DXX) DOOR NUMBER

1A APARTMENT NO.

SYMBOL & LETTER

WINDOW NUMBER

CAST-IN PLACE CONCRETE

PLYWOOD

BATT INSULATION

BLOCKING or ROUGH WOOD


NEW INTERIOR PARTITION

CONCRETE MASONRY UNIT

---- PROPERTY LINE

WATER LINE

---- SOFFIT LINE



GENERAL NOTES

ALL WORK SHALL CONFORM TO THE 2022 CONNECTICUT STATE BUILDING CODE AND, TOWN OF WESTPORT MUNINCIPAL CODE & ALL RULES AND REGULATIONS OF ALL DEPARTMENTS HAVING JURISDICTION.

THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR THE VERIFICATION OF ALL DIMENSIONS AND JOB CONDITIONS.

THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL PERMITS.

CONDITIONS PRIOR TO SUBMITTING A PRICE TO THE OWNER.

THE RIGHT TO ORDER REMOVAL OF DEFECTIVE WORK AND MATERIALS.

THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR SITE SECURITY AND JOB SAFETY. CONSTRUCTION SHALL BE IN ACCORDANCE WITH OSHA REGULATIONS AND STANDARDS AND ALL LOCAL REQUIREMENTS.

THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE TO FOLLOW ALL SAFE EXCAVATION PRACTICES AND CALL "DIG-SAFELY" AT LEAST 3 WORKING DAYS IN ADVANCE TO MARK UP ANY UNDERGROUND UTILITIES. NO EXCAVATION WORK OR DIGGING OF ANY KIND SHALL START OTHERWISE.

ALL WORK SHALL BE PERFORMED IN A WORKMAN-LIKE MANNER BY QUALIFIED JOURNEYMEN OR MASTERS OF EACH TRADE.

ALL MATERIAL HANDLING AND INSTALLATION SHALL BE STRICTLY IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.

GENERAL CONTRACTOR SHALL BE RESPONSIBLE, AND PAY FOR ALL TESTS, INSPECTIONS, ETC. AS REQUIRED BY THE BUILDING DEPARTMENT AND ANY OTHER DEPARTMENTS HAVING JURISDICTIONS.

GENERAL CONTRACTOR SHALL VISIT THE SITE AND MAKE HIMSELF FAMILIAR WITH THE WORK AND THE LOCAL

ALL SURFACES ADJACENT TO THE WORK AREA, WHICH IS DAMAGED DURING CONSTRUCTION BY THE FORCES OF THE GENERAL CONTRACTOR, SHALL BE REPAIRED TO MATCH SURROUNDING SURFACES TO SATISFACTION OF THE OWNER AND ARCHITECT AT NO ADDITIONAL COST.

THE CONTRACTOR SHALL REMOVE FROM THE ALL DEBRIS CREATED BY HIS WORK AND SHALL DISPOSE OF THEM IN A LEGAL MANNER ON A WEEKLY BASIS OR SOONER AS CONDITIONS WARRANTS.

at completion of the work the Site Shall be cleared of all debris and remaining materials and

THE PREMISES SHALL BE LEFT BROOM CLEAN. THE ENGINEER SHALL BE THE SOLE JUDGE AS TO THE ADEQUACY OF THE WORK PERFORMED. HE SHALL HAVE

ANY DEVIATION FROM THESE DRAWINGS SHALL CAUSE THE WORK TO CEASE IN THE AFFECTED AREAS UNTIL

THE ENGINEER HAS APPROVED THE CHANGES.

NO DRAWINGS SHALL BE USED ON JOB UNLESS THEY BEAR THE STAMP: ISSUED FOR CONSTRUCTION.

ENGINEER OF RECORD NOT RESPONSIBLE FOR FILING OR OBTAINING ANY APPROVALS WITH ANY BOARD.

CONTRACTOR IS CAUTIONED TO MAKE CONTINUOUS OBSERVATION OF THE EXISTING STRUCTURE DURING THE PERFORMANCE OF HIS WORK. SHOULD HE BECOME AWARE OF ANY SITUATION THAT REQUIRES FURTHER INVESTIGATION (SUCH AS CRACKS IN MASONRY AND PARTITIONS, ADDITIONAL OR EXCESSIVE DEFLECTION, ETC.) HE SHALL NOTIFY THE ENGINEER.

CONSTRUCTION NOTES

TEMPORARY SHORING: PROVIDE AND MAINTAIN SHORING, BRACING. AND STRUCTURAL SUPPORTS AS REQUIRED TO PRESERVE STABILITY AND PREVENT MOVEMENT, SETTLEMENT, OR COLLAPSE OF CONSTRUCTION AND FINISHES TO REMAIN, AND TO PREVENT UNEXPECTED OR UNCONTROLLED MOVEMENT OR COLLAPSE OF CONSTRUCTION BEING DEMOLISHED.

DO NOT USE CUTTING TORCHES UNTIL WORK AREA IS CLEARED OF FLAMMABLE MATERIALS. AT CONCEALED SPACES, SUCH AS JOUCT AND PIPE INTERIORS, VERIFY CONDITION AND CONTENTS 'OF HIDDEN SPACE BEFORE STARTING FLAME-CUTTING OPERATIONS. MAINTAIN FIRE WATCH AND PORTABLE FIRE-SUPPRESSION DEVICES DURING FLAME-CUTTING OPERATIONS.

LOCATE DEMOLITION EQUIPMENT AND REMOVE DEBRIS AND MATERIALS SO AS NOT TO IMPOSE EXCESSIVE LOADS ON SUPPORTING WALLS, FLOORS. OR FRAMING.

PROTECT CONSTRUCTION INDICATED TO REMAIN AGAINST DAMAGE AND SOILING DURING DEMOLITION.

OWNER APPROVAL IS REQUIRED PRIOR TO PROPOSED INSTALLATION OF THE CONSTRUCTION FENCE ON

CONTRACTOR SHOULD OBTAIN A PERMISSION TO ENTER ADJOINING PROPERTIES AND PRECONSTRUCTION SURVEY OF EXISTING CONDITIONS SHOULD BE CONDUCTED OVER ADJOINING PROPERTIES AND A WRITTEN AND PHOTOGRAPHIC DOCUMENTATION SHOULD BE OBTAINED PRIOR TO COMMENCEMENT OF ANY OPERATION. ADJOINING PROPERTY OWNERS, PROFESSIONAL ENGINEER INVOLVED IN THE PROJECT SHOULD BE NOTIFIED OF ANY ONGOING PROBLEM OR ANY OTHER PARTICULAR SITUATION THAT COULD ARISE

A QUALIFIED ENGINEER SHALL BE ON SITE FOR ANY REQUIRED CONTROL INSPECTION AND TO SURVEY CONDITIONS OF BUILDING OR STRUCTURE TO BE REMOVED AND DETERMINE WHETHER REMOVING ANY ELEMENT MIGHT RESULT IN STRUCTURAL DEFICIENCY OR UNPLANNED COLLAPSE OF ANY PORTION OF STRUCTURE OR ADJACENT STRUCTURES DURING DEMOLITION OPERATIONS.

BEFORE STARTING OPERATIONS, PROVIDE THE NECESSARY PROTECTIVE ELEMENTS, WHERE REQUIRED, IN STRICT ACCORDANCE WITH OSHA RULES AND REGULATIONS. COMPLY WITH GOVERNING EPA NOTIFICATION REGULATIONS BEFORE BEGINNING DEMOLITION. COMPLY WITH HAULING AND DISPOSAL REGULATIONS OF AUTHORITIES HAVING JURISDICTION AND ALL EXPRESSED IN THE NOTES. COMPLY WITH ANSI A10.6 AND NFPA 241.

SPRAY FOAM INSULATION TO TJI FLOOR JOISTS PROVIDED.

CARPENTRY NOTES

DURING THE DEMOLITION OPERATIONS.

ADJACENT PROPERTIES.

PROVIDE ALL BLOCKING AND CUT OUTS AS REQUIRED FOR MEDICINE CABINETS, ACCESS DOORS AS REQUIRED, PLUMBING FIXTURES, H.V.A.C., ETC. VERIFY WITH ARCHITECT AND OWNER PRIOR TO START OF CARPENTRY WORK.

THE CARPENTRY CONTRACTOR SHALL BE RESPONSIBLE TO THE LEVEL OF ALL FLOORS, SILLS, ETC. AND PLUMBING OF ALL WALLS, JAMBS, ETC.

ALL FINISHED HARDWARE SHALL BE SUPPLIED AND INSTALLED BY THE CARPENTRY CONTRACTOR. THE CARPENTRY CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY TEMPLATES, ETC. AND INSURE THE PROPER INSTALLATION OF ALL FINISHED HARDWARE. CARPENTRY CONTRACTOR SHALL PROVIDE BRASS BUTTS, 180 DEGREE SWING, MINIMUM THREE PER DOOR.

ELECTRICAL NOTES

1. ALL WORK SHALL BE PERFORMED IN STRICT ACCORDANCE WITH THE REQUIREMENTS OF THE 2017 NATIONAL ELECTRICAL CODE, VA STANDARDS, THE APPLICABLE SECTIONS OF THE NFPA 101 AND NFPA 72, AND ALL GOVERNING LOCAL CODES, LAWS, AND REGULATIONS.

2. PROVIDE A COMPLETE OPERABLE SYSTEM IN A WORKMANLIKE MANNER. OUTLINE DESCRIPTION AND EQUIPMENT LAYOUT DO NOT LIMIT CONTRACTOR'S LIABILITY FOR THE INSTALLATION OF A COMPLETE OPERABLE SYSTEM.

MINIMUM SIZE OF CONDUITS SHALL BE 3/4", UNLESS OTHERWISE NOTED.

4. NO CONDUIT SHALL BE RUN IN ANY FLOOR IN CONTACT WITH THE EARTH UNLESS OTHERWISE DIRECTED ON THE PLANS.

5. CONDUIT RUNS SHALL CLEAR ALL ARCHITECTURAL FEATURES (DOORS, WINDOWS, ETC) AND SHALL BE COORDINATED WITH EXISTING OR NEW EQUIPMENT, PIPING AND DUCT WORK CORRESPONDING TO ALL TRADES INCLUDING BUT NOT LIMITED TO MECHANICAL, PLUMBING, FIRE PROTECTION AND ELECTRICAL TRADES. NOTIFY THE PROJECT ENGINEER OF ANY OBSTRUCTION BEFORE INSTALLATION. FAILURE TO COMPLY WITH THIS REQUIREMENT WILL NOT BE CONSIDERED ADDITIONAL WORK AND SHALL BE CORRECTED AT NO ADDITIONAL COST TO THE OWNER.

6. RACEWAY INSTALLED EXPOSED ON THE SURFACE OF CEILINGS OR SIDEWALLS SHALL BE SUPPORTED FROM STRUCTURAL COMPONENTS OF THE BUILDING.

7. ALL RACEWAYS AND CABINETS SHALL BE GROUNDED TO THE BUILDING GROUNDING SYSTEM WITH AN INSULATED GROUND CONDUCTOR NOT SMALLER THAN #10 U.O.N.

8. ALL ELECTRICAL EQUIPMENT AND RACEWAY SHALL BE SUSPENDED FROM SUPPLEMENTAL SLOTTED CHANNEL FRAME. ALL SUCH MOUNTS, DEVICES, FASTENERS SHALL BE OF SUFFICIENT THICKNESS TO CARRY THE LOAD SUSPENDED AND SHALL BE SEISMICALLY RESTRAINED. CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING ANY ADDITIONAL SUPPLEMENTAL STEEL REQUIRED TO SUPPORT THE EQUIPMENT OR DEVICES.

9. ALL OPENINGS BETWEEN FLOORS, THROUGH RATED FIRE AND SMOKE WALLS, CREATED BY THE CONTRACTOR FOR CABLE OR CONDUIT PASS THROUGH SHALL BE SEALED WITH A FIRE STOPPING MATERIAL. FIRE STOPPING MATERIAL AND ITS APPLICATION SHALL BE ACCOMPLISHED IN SUCH A MANNER THAT IS ACCEPTABLE TO THE LOCAL FIRE AND BUILDING AUTHORITIES HAVING JURISDICTION OVER THIS WORK. ANY OPENINGS CREATED BY OR FOR THE CONTRACTOR AND LEFT UNUSED SHALL ALSO BE SEALED AS PART OF THIS WORK.

10. CONTRACTOR TO BE RESPONSIBLE FOR ALL RESTORATIONS, SEALING, WATERPROOFING, PENETRATIONS, CORE DRILLING CUTTING, PATCHING, AND PAINTING FOR THE COMPLETE CONTRACT WORK INDICATED. ALL RESTORATION WORK PERFORMED BY CONTRACTOR SHALL RESTORE DISTURBED SURFACES TO THEIR ORIGINAL CONDITION.

PLUMBING NOTES

REFER TO ARCHITECTURAL DRAWINGS FOR EXACT LOCATION OF ALL FIXTURES, OUTLETS AND ACCESSORIES, INCLUDING FLOOR DRAINS.

PROVIDE & INSTALL ALL ACCESS DOORS FOR CEILING AND WALL ACCESS TO ALL PIPING AND VALVES REQUIRING SERVICE.

CONTRACTOR IS RESPONSABLE FOR ALL CHANGES TO WORK OF ALL TRADES NECESSITATED BY PROVIDING EQUIPMENT DIFFERING IN ANY RESPECT FROM THAT INDICATED.

ALL EQUIPMENT SHALL BE SELECTED TO FIT AVAILABLE SPACE.

COORDINATE ALL PLUMBING REQUIREMENTS WITH THE CITY OF YONKERS FILE FOR AND PAY ALL PERMITS.

PLUMBING WORK SHALL BE PERFORMED BY FAIRFIELD COUNTY LICENSED PLUMER UNDER SEPARATE PERMIT.

MECHANICAL NOTES

ME.1 ALL GAS AND OIL BURNING EQUIPMENT SHALL CONFORM TO THE CONNECTICUT STATE BUIDLING

ME.2 ALL BOILER AND FURNACE ROOM SHALL BE AS PER NYS BUILDING CODE.

ME.3 ALL DUCTWORK LOCATED IN UNAIRCONDITIONED OR UNHEATED SPACES, SHALL BE SEALED AND INSULATED AS PER NYS ENERGY CODE.

VENTILATION NOTES

V.1 THESE DWGS COMPLY OR EXCEED THE MINIMUM REQUIREMENTS FOR LIGHT, HEAT, VENTILATION & NOISE CONTROL AS PER THE CONNECTICUT STATE BUILDING CODE.

SMOKE DETECTOR NOTES:

DWELLING UNITS SHALL BE EQUIPPED WITH SMOKE DETECTORS RECEIVING ITS PRIMARY POWER FROM THE BUILDING WIRING AND THERE SHALL NOT BE ANY SWITCHES IN THE CIRCUIT OTHER THAN THE OVER CURRENT DEVICE PROTECTING THE BRANCH CIRCUIT.

ALL SMOKE DETECTING DEVICES SHALL BE APPROVED BY A NATIONALLY RECOGNIZED INDEPENDENT LABORATORY THAT STATES IN LISTINGS THAT THE EQUIPMENT MEETS NATIONALLY RECOGNIZED STANDARDS.

THE DEVICE SHALL BE OF EITHER THE IONIZATION CHAMBER OF PHOTOELECTRIC TYPE.

SPRAY FOAM INSULATION PROVIDED.

GAS PIPING NOTES

GP.1 MATERIAL: THREADED, OUTDOOR SHALL BE COVER MINIMUM INSIDE THE BUILDING.

GP.2 GAS PIPING SHALL BE INSTALLED BY A LICENSED PLUMBER AND WITH STANDARD OF THE COMPANY WHICH SUPPLIES THE GAS SERVICE

GP.3 THE PLUMBING CONTRACTOR SHALL MAKE ALL ARRANGEMENTS NECESSARY TO BRING THE GAS SERVICE INTO THE BUILDING & HE/SHE SHALL ASCERTAIN THAT MATERIAL AND LABOR MATCH THE SPECIFICATIONS OF THE COMPANY WHICH SUPPLIES THE GAS. THE MECHANICAL CONTRACTOR SHALL PAY FOR AND SECURE ANY NECESSARY APPROVAL PERMITS AND INSPECTIONS REQUIRED BEFORE STARTING THE WORK, AND AFTER ITS COMPLETION.

GP.4 GAS PIPING SHALL BE CAREFULLY TESTED FOLLOWING THE PROCEDURE SPECIFIED BY THE LOCAL REGULATIONS AND CODES.

GP.5 WHERE GAS PIPE IS TO BE ENCLOSED, THE PIPE TEST MUST PRECEDE THE WORK OF ENCLOSURE.

GP.6 ALL GAS PIPING, GAS SERVICE PIPING, GAS METER LOCATION, GAS PIPING MATERIAL SHALL COMPLY WITH NYC PLUMBING CODE.

ENERGY CONSERVATION

E1. DESIGN OF INSIDE AIR TEMPERATURE OF EACH ROOM THAT IS HEATED AND/OR COOLED:

HEATED 72 F° (MAX. NYS) COOLED 75 F° (MIN. NYS)

E2. ALL INSULATION WHICH IS CAPABLE OF ABSORBING WATER SHALL BE PROTECTED BY A VAPOR BARRIER LOCATED ON THE WINTER WARM SIDE OF THE INSULATION, INSULATION SHALL BE INSTALLED IN A MANNER THAT PROVIDES CONTINUITY OF INSTALLATION AT PLATE LINES, SILL LINES AND CORNERS.

E3. LOCAL ENERGY CONSERVATION CONSTRUCTION CODE

LOCAL ENERGY CONSERVATION CONSTRUCTION CODES THAT ARE MORE STRINGENT IN THEIR REQUIREMENTS THAN THE NEW YORK STATE ENERGY CONSERVATION CONSTRUCTION CODE SHALL APPLY AND BE IMPLEMENTED WHEREVER REQUIRED.

E4. AIR LEAKAGE FOR ALL BUILDINGS ALL EXTERIOR DOORS AND WINDOWS SHALL BE DESIGNED TO LIMIT AIR LEAKAGE INTO OR OUT OF THE BUILDING ENVELOPE. MANUFACTURED DOORS AND WINDOWS SHALL HAVE AIR INFILTRATION RATES NOT EXCEEDING THOSE SHOWN THE NYS ENERGY CODE. SITE CONSTRUCTED DOORS AND WINDOWS SHALL BE SEALED IN ACCORDANCE WITH THE NYS ENERGY CODE.

E5. EXTERIOR JOINTS AROUND WINDOWS AND DOOR FRAMES, OPENINGS BETWEEN WALL AND ROOF/CEILING, FLOORS AND ROOFS, AND ALL OTHER SUCH OPENINGS IN THE BUILDING ENVELOPE SHALL BE CAULKED, GASKETED, WEATHERSTRIPPED OR OTHERWISE SEALED.

E6. SHOWERS, OTHER THAN THOSE USED FOR SAFETY REASONS, SHALL BE EQUIPPED WITH OUTLET DEVICES WHICH LIMIT THE FLOW OF HOT WATER TO A MAXIMUM OF 3 GPM AT A CONSTANT WATER PRESSURE OF 60 PSI.

E7. DESIGN PROFESSIONAL STATES THAT TO THE BEST OF HIS KNOWLEDGE AND PROFESSIONAL JUDGEMENT, THE DESIGN HAS BEEN MADE IN CONFORMANCE WITH THE ENERGY CODE.

E8. THIS DESIGN ANALYSIS IS NOT TO BE USED AS THE DETERMINING FACTOR IN COMPUTING THE DESIGN OF THE HEATING AND/OR VENTILATING EQUIPMENT TO BE INSTALLED IN THE BUILDING. TO DO SO WILL BE AT THE BUILDER AND/OR CONTRACTOR'S RISK. THE ARCHITECT OR ENGINEER SHALL BE HELD BLAMELESS FOR ANY HEATING OR VENTILATING EQUIPMENT INSTALLED AT THE JOB SITE.

E9. PROVIDE AT LEAST ONE PROGRAMMABLE THERMOSTAT FOR EACH SEPARATE COOLING AND HEATING SYSTEM.

E10. PROVIDE R=6 MIN INSULATION AROUND DUCTS EXCEPT IN ATTIC, PROVIDE R=8 MIN. PROVIDE R=3 INSULATION AROUND ALL PIPING THAT CARRY FLUIDS WITH A TEMPERATURE OF MORE THAN 105F OR LESS THAN 55F.

E11. WINDOW INFILTRATION SHALL NOT EXCEED .5 CFM PER LINEAR FOOT OF CRACK WHEN TESTED AT IMPACT PRESSURE OF 25 MPH WIND.

E12. DOOR INFILTRATION SHALL NOT EXCEED 1.0 CFM PER LINEAR FOOT OF CRACK WHEN TESTED AT IMPACT PRESSURE OF 25 MPH WIND.

E13. THE BUILDING IS LOCATED IN CLIMATE ZONE 4 AND ITS THERMAL ENVELOPE SHALL MEET THE REQUIREMENTS BY COMPONENTS OF NYS ENERGY CODE FOR FENESTRATION AND INSULATION.

NYS ECC PROFESSIONAL STATEMENT:

I, Shahin Badaly, do hereby certify to the best of my knowledge, belief and professional JUDGMENT, THESE PLANS AND SPECIFICATIONS ARE IN COMPLIANCE WITH THE 2022 CONNECTICUT STATE BUILDING CODE, CLIMATE ZONE 4A."

FIRE STOPPING NOTES

FS.1 DUCT AND PIPE SPACES AND CONCEALED SPACES WITHIN PARTITIONS, WALLS, FLOORS, ROOFS, STAIRS, FURRING, PIPE SPACES, COLUMN ENCLOSURES, ETC. THAT WOULD PERMIT PASSAGE OF FLAME, SMOKE, FUMES, OR HOT GASES FROM ONE FLOOR TO ANOTHER FLOOR OR ROOF SPACES, OR FROM ONE CONCEALED AREA TO ANOTHER, SHALL BE FILLED WITH NON-COMBUSTIBLE MATERIAL.

FS.2 FIRE STOPPING MAY BE OF COMBUSTIBLE MATERIALS CONSISTING OF WOOD NOT LESS THAN 2" NOMINAL THICKNESS WITH TIGHT JOINTS WHERE USED IN COMBUSTIBLE CONSTRUCTION, EXCEPT THAT NON-COMBUSTIBLE FIRE STOPPING SHALL BE USED IN CONCEALED SPACES OF FIRE DIVISIONS AND WHERE IN CONTACT WITH FIREPLACES, FLUES, AND CHIMNEYS.

FS.3 ALL HOLLOW PARTITIONS AND FURRED OUT SPACES SHALL BE FIRE STOPPED AT EACH FLOOR LEVEL. FIRE STOPS SHALL BE THE FULL THICKNESS OF THE HOLLOW FURRED OUT SPACES.

FS.4 CONCEALED SPACES WITHIN STAIRS CONSTRUCTION SHALL BE FIRE STOPPED BETWEEN STRINGERS AT THE TOP AND BOTTOM OF EACH FLIGHT OF STAIRS SO AS NOT TO COMMUNICATE WITH SPACES IN THE FLOOR, ROOF, OR INTERMEDIATE LANDING CONSTRUCTION.

FS. 5CEILINGS THAT CONTRIBUTE TO THE REQUIRED FIRE-RESISTANT RATING OF A FLOOR OR ROOF ASSEMBLY SHALL BE CONTINUOUS BETWEEN EXTERIOR WALLS, VERTICAL FIRE DIVISIONS, FIRE SEPARATIONS, CORRIDOR PARTITIONS OR ANY OTHER PARTITIONS HAVING AT LEAST THE SAME FIRE RESISTANCE RATING AS THE CEILING. THE CONCEALED SPACE ABOVE SUCH CEILING SHALL BE FIRE STOPPED INTO AREAS NOT EXCEEDING 3,000 SQ. FT. FOR THE FULL HEIGHT OF THE CONCEALED SPACE.

WORK TO BE FILED UNDER SEPERATE APPLICATIONS:

1. ELECTRICAL PERMIT

2. PLUMBING PERMIT

3. POOL PERMIT

4. HVAC

N O TES		
D, BLACK STEEL, SCHEDULE 40 PIPE, WITH IRON FITTING. GAS PIPING INSTALLED	ENERGY ANALYSIS	
ERED WITH TWO COATS OF PAINTING, WHICH SHALL BE EXTENDED @ 3 INCHES	ITEM DESCRIPTION	PROPOSED DESIGN

ENERGY ANALYSIS		
ITEM DESCRIPTION	PROPOSED DESIGN VALUE	CODE PRESCRIPTIVE VALUE AND CITATION
FURNACE	97.4% AFUE	80% AFUE
COIL	18.0 SEER	13.0 SEER

LAW ARTICLE 145, SECTION 7209.

BADALY ENGINEERING PLLC

ny alterations of these plans, unless done by c INDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATIO

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCEI OPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN AN' AY EXPLOITED WITHOUT WRITTEN PERMISSION FROM ADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



peter klein , associates, ARCHITECTS - BUILDERS - DEVELOPER CONSTRUCTION MANAGEMENT

CEL. 914-6181847

PDLPARCHITECTURE@HOTMAIL.COM

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

DATE DESCRIPTION # DATE DESCRIPTION


NEW SINGLE FAMILY RESIDENCE:

<u>1A PLUNKETT PL</u> WESTPORT, CT 10708

DRAWING TITLE:

GENERAL NOTES

AS NOTED 02/13/23 JOB NO.: 22335 RAWN BY HECKED B



DRAWING NO.:

2 OF 36

CLIMATIC AND GEOGRAPHIC DESIGN CRITERIA

GROUND		WIND [DESIGN		05107410	SUBJEC	T TO DAMAG	E FROM	\.(\)\.\.\.\.\.\.\.\.\.\.\.\.\.\.\.\.\.\			,	
snow load (PSF)	SPEED (MPH)	TOPOGRAPHIC EFFECTS	SPECIAL WIND REGION	WIND-BORNE DEBRIS ZONE	SEISMIC DESIGN CATEGORY	WEATHERING	FROST LINE DEPTH	TERMITE	WINTER DESIGN TEMP	ICE BARRIER UNDERLAYMENT REQUIRED	FLOOD HAZARDS	AIR FREEZING INDEX	MEAN ANNUAL TEMP
30 PSF	120	NO	YES	30 PSF	В	SEVERE	3'-6"	MODERATE TO HEAVY	7 DEG. F	YES	SEE BELOW	1500	50 DEG. F

FLOOD HAZARDS:


(a) FIRST CODE DATE OF ADOPTION JULY 9,1980.

(b) DATE of FLOOR INSURANCE STUDY JAN. 21, 1998.

(c) MAP PANEL NUMBERS 36119C0907F THROUGH 36119C0338F EFFECTIVE SEPT. 28, 2007.

Property Address(es):	1 A PLUNKETT PL			
Zoning District(s):	AA			
Structure / Site Use(s):	1-FAMILY DWELLING			
<u>Item</u>	Required / Permitted	<u>Existing</u>	<u>Proposed</u>	<u>Variance</u> <u>Requested</u>
Building Height (stories)	3	2	2	NO
Building Height (feet)	40	24.88	30.16	NO
Lot Coverage - Impervious Surface (%)	25%	13.78%	16.7%	NO
Lot Area (square feet)	43,560	44,098	44,098	NO
Front Yard Setback (feet)	30	38.60	34.08	NO
Front Yard Setback-Secondary (feet)	30	91.30	91.30	NO
Side Yard Setback (feet)	25	34.50	26.50	NO
Rear Yard Setback	25	n/a	n/a	NO
Number of Off-Street Parking Spaces	2	2 (Garage)	3 (Garage)	NO

NOTE: EXISTING ZONING REGULAITON VALUES OBTAINED FROM SURVEY PREPARED BY WALTER H. SLIDD - LAND SURVEYOR LLC DATED: NOV. 17, 2022



ENGINEERING DESIGN:

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

(914) 465-9010 ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PATRICIA DE LA PUENTE PRINCIPAL
CEL. 914-6181847
PDLPARCHITECTURE@HOTMAIL.COM

PETER KLEIN , ASSOCIATES, INC ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

ISSU	JES:	
#	DATE	DESCRIPTION
REV	<u>'ISIONS:</u>	
#	DATE	DESCRIPTION


PROJECT TITLE:


NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TITLE:


SITE PLAN & ZONING <u>COMPLIANCE</u>





A-100.00





EXISTING BASEMENT FLOOR PLAN
Scale: 1/4" = 1'-0"

ENGINEERING DESIGN:

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

(914) 465-9010 ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PATRICIA DE LA PUENTE

PRINCIPAL
CEL. 914-6181847
PDLPARCHITECTURE@HOTMAIL.COM

Peter Klein , associates, inc ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

ISSU	IES:	
#	DATE	DESCRIPTION
REV	<u>'ISIONS:</u>	
#	DATE	DESCRIPTION

NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TITLE:

EXISTING FLOOR <u>PLANS</u>


DRAWN BY



DRAWING NO.:

A-110.00

FINISH SCHEDULE								<u>LEGEND</u>	
LOCATION	WALLS	CEILING	FLOOR	COUNTER	BASE TRIM	DOOR & WINDOW TRIM	NOTES	SD SMOKE DETECTOR, HARD WIRED W/ BATTERY BACK UP	EXISTING PARTITION TYPE TO REMAIN
KITOLIFAL	PAINTED G.W.B.	DAINITED C W D	CEDALAIC THE	OLIA DIZ	0/1/15-1/41/05/15	9/16"x3-1/4" COLONIAL	PROVIDE MOLD & MILDEW RESISTANT	SD COMBINATION SMOKE AND CARBON MONOXIDE	
CERAMIC TILE ON CEMENT BACKERBOARD AT BACK.	CERAMIC TILE ON CEMENT BACKERBOARD AT BACKSPLASH	PAINTED G.W.B.	W.B. CERAMIC TILE	QUARTZ	9/16"x5-1/4" PINE		G.W.B. BEHIND SINK BASE CABINET.	DETECTOR, HARD WIRED W/ BATTERY BACK UP	PROPOSED EXTERIOR PARTITION
BATHROOM	CERAMIC TILE ON CEMENT BACKERBOARD AT HALF WAY HEIGHT & PAINTED G.W.B. TO BE INSTALLED UP TO CEILING HEIGHT. CERAMIC TILE ON CEMENT BACKERBOARD AT TUB/SHOWER	PAINTED G.W.B.	CERAMIC TILE	CERAMIC W/ BASIN	CERAMIC TILE	9/16"x3-1/4" COLONIAL	G.W.B.	HEAT DETECTOR. INTERCONNECTED TO SMOKE DETECTOR, HARD WIRED W/ BATTERY BACK UP	PROPOSED INTERIOR PARTITION
ALL OTHER ROOMS	ENCLOSURES TO BE INSTALLED UP TO CEILING HEIGHT. PAINTED G.W.B.	PAINTED G.W.B.	3/4"x5" WHITE OAK	N/A	9/16"x5-1/4" PINE	9/16"x3-1/4" COLONIAL CASING PINE	THROUGHOUT.	100 CFM VENTILATION FAN. WIRE TO VANITY LIGHT SWITCH AT BATHROOM. VENT DIRECTLY TO EXTERIOR. CORROSION-RESISTANT SCREEN AT TERMINATION.	



ENGINEERING DESIGN:

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

(914) 465-9010 ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PRINCIPAL
CEL. 914-6181847
PDLPARCHITECTURE@HOTMAIL.COM Peter Klein , associates, in ARCHITECTS - BUILDERS - DEVELOPERS

44 WINDING WOOD ROAD

CONSTRUCTION MANAGEMENT

RYE BROOK , NEW YORK 10573


1330	<u>/E3.</u>	
#	DATE	DESCRIPTION
REV	<u>'ISIONS:</u>	
#	DATE	DESCRIPTION
	 	

NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TITLE:


BASEMENT FLOOR <u>PLAN</u>



DRAWING NO.:

5 OF 36

BASEMENT FLOOR PLAN
Scale: 1/4" = 1'-0"



BADALY ENGINEERING PLLC

914) 465-9010 any alterations of these plans, unless done by oi

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PDLPARCHITECTURE@HOTMAIL.COM PETER KLEIN , ASSOCIATES, IN ARCHITECTS - BUILDERS - DEVELOPERS

CEL. 914-6181847

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

DESCRIPTION DESCRIPTION

NEW SINGLE FAMILY RESIDENCE:


<u>1A PLUNKETT PL</u> WESTPORT, CT 10708

FIRST FLOOR PLAN

SEAL AND SIGNATURE:

A-112.00

FINISH SCHEDULE								LEGEND	
LOCATION	WALLS	CEILING	FLOOR	COUNTER	BASE TRIM	DOOR & WINDOW TRIM	NOTES	SD SMOKE DETECTOR, HARD WIRED W/ BATTERY BACK UP	EXISTING PARTITION TYPE TO REMAIN
KITCHEN	PAINTED G.W.B.	DAINITED CAM D	CEDALAIC THE	OHADI7	0/1/45-1/45-01/5	9/16"x3-1/4" COLONIAL	PROVIDE MOLD & MILDEW RESISTANT	SD) COMBINATION SMOKE AND CARBON MONOXIDE	
CERAMIC TILE ON CEMENT BA	CERAMIC TILE ON CEMENT BACKERBOARD AT BACKSPLASH	PAINTED G.W.B.	CERAMIC TILE	QUARTZ	9/16"x5-1/4" PINE		G.W.B. BEHIND SINK BASE CABINET.	COMBINATION SMOKE AND CARBON MONOXIDE DETECTOR, HARD WIRED W/ BATTERY BACK UP	PROPOSED EXTERIOR PARTITION
BATHROOM	CERAMIC TILE ON CEMENT BACKERBOARD AT HALF WAY HEIGHT & PAINTED G.W.B. TO BE INSTALLED UP TO CEILING HEIGHT. CERAMIC TILE ON CEMENT BACKERBOARD AT TUB/SHOWER	PAINTED G.W.B.	CERAMIC TILE	CERAMIC W/ BASIN	CERAMIC TILE	9/16"x3-1/4" COLONIAL	PROVIDE MOLD & MILDEW RESISTANT G.W.B.	HEAT DETECTOR. INTERCONNECTED TO SMOKE DETECTOR, HARD WIRED W/ BATTERY BACK UP	PROPOSED INTERIOR PARTITION
	ENCLOSURES TO BE INSTALLED UP TO CEILING HEIGHT.					9/16"x3-1/4" COLONIAL	THROUGHOUT.	100 CFM VENTILATION FAN. WIRE TO VANITY LIGHT SWITCH AT BATHROOM. VENT DIRECTLY TO EXTERIOR.	
ALL OTHER ROOMS	PAINTED G.W.B.	PAINTED G.W.B.	3/4"x5" WHITE OAK	N/A	9/16"x5-1/4" PINE	CASING PINE	-	CORROSION-RESISTANT SCREEN AT TERMINATION.	



BADALY

ENGINEERING DESIGN:

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

(914) 465-9010 BADALY.COM

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PETER KLEIN, ASSOCIATES, INC ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

ISSU	JES:	
#	DATE	DESCRIPTION
<u>RE\</u>	/ISIONS:	
#	DATE	DESCRIPTION
PRO	DJECT TITLE:	

NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TITLE:

SECOND FLOOR PLAN


SCALE:
AS NOTED

DATE:
02/13/23

JOB NO.:
22335

DRAWN BY:
AK

DRAWING NO.:




A-113.00

^{o..} 7 OF 36

SECOND FLOOR PLAN
Scale: 1/4" = 1'-0"

FINISH SCHEDULE								LEGENI
LOCATION	WALLS	CEILING	FLOOR	COUNTER	BASE TRIM	DOOR & WINDOW TRIM	NOTES	SD SA
VITÇUENI	PAINTED G.W.B.	PAINTED G.W.B.	CERAMIC TILE	QUARTZ	9/16"x5-1/4" PINE		PROVIDE MOLD & MILDEW RESISTANT	(SD) Co
KITCHEN	CERAMIC TILE ON CEMENT BACKERBOARD AT BACKSPLASH	PAINIED G.W.B.	CERAMIC TILE	QUARIZ	7/10 XJ-1/4 FINE	CASING PINE	G.W.B. BEHIND SINK BASE CABINET.	SD CO
R ATHPOONA	CERAMIC TILE ON CEMENT BACKERBOARD AT HALF WAY HEIGHT & PAINTED G.W.B. TO BE INSTALLED UP TO CEILING HEIGHT.	PAINTED G.W.B.	CERAMIC TILE	CERAMIC W/ BASIN	CERAMIC TILE	9/16"x3-1/4" COLONIAL	PROVIDE MOLD & MILDEW RESISTANT	HD HE
BATHROOM	CERAMIC TILE ON CEMENT BACKERBOARD AT TUB/SHOWER ENCLOSURES TO BE INSTALLED UP TO CEILING HEIGHT.	TRAINIED G.W.B.	V.B. CERAMIC IILE	CERAMIC W/ BASIN	CERAMIC TILE	CASING PINE	G.W.B. THROUGHOUT.	10
ALL OTHER ROOMS	PAINTED G.W.B.	PAINTED G.W.B.	3/4"x5" WHITE OAK	N/A	9/16"x5-1/4" PINE	9/16"x3-1/4" COLONIAL CASING PINE	-	SW CC

- ETECTOR, HARD WIRED W/ BATTERY
- ATION SMOKE AND CARBON MONOXIDE R, HARD WIRED W/ BATTERY BACK UP
- ECTOR. INTERCONNECTED TO SMOKE R, HARD WIRED W/ BATTERY BACK UP
- VENTILATION FAN. WIRE TO VANITY LIGHT T BATHROOM. VENT DIRECTLY TO EXTERIOR. ON-RESISTANT SCREEN AT TERMINATION.






ENGINEERING DESIGN:

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

(914) 465-9010 ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



DE LA PUENTE ARC-CONSULTANT, LLC

PATRICIA DE LA PUENTE PRINCIPAL
CEL. 914-6181847
PDLPARCHITECTURE@HOTMAIL.COM

Peter Klein , associates, inc ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

ISSU	JES:	
#	DATE	DESCRIPTION
REV	<u> ISIONS:</u>	
#	DATE	DESCRIPTION


NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TITLE:

ATTIC PLAN





SHEET NO.: 8 OF 36





ELEVATION LEGEND:

- 1. ASPHALT ROOF SHINGLES
- 2. WOOD FASCIA BOARD
- 3. 5" O.G. GUTTER
- 4. HARDIE-PLANK SIDING
- 5. HARDIE-PLANK SIDING TRIM
- 7. VINYL WINDOWS
- 8. ENTRY DOOR
- 9. WOOD POST
- 10. CEMENTITIOUS STUCCO
- 12. TREX RAILING
- 13. CONC. SLAB ON GRADE
- 14. CONC. SONOTUBE

DE LA PUENTE ARC-CONSULTANT, LLC PATRICIA DE LA PUENTE

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT

ENGINEERING DESIGN:

(914) 465-9010

Peter Klein , associates, in ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

CEL. 914-6181847
PDLPARCHITECTURE@HOTMAIL.COM

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

ELEVATION LEGEND:

1. ASPHALT ROOF SHINGLES

2. WOOD FASCIA BOARD

3. 5" O.G. GUTTER

4. HARDIE-PLANK SIDING 5. HARDIE-PLANK SIDING TRIM

6. STANDING SEAM METAL ROOFING

7. VINYL WINDOWS

8. ENTRY DOOR

9. WOOD POST


10. CEMENTITIOUS STUCCO

11. WOOD DECK W/ TREX DECKING PANELS

12. TREX RAILING

13. CONC. SLAB ON GRADE

14. CONC. SONOTUBE



1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TITLE:

FRONT & REAR BUILDING ELEVATION

AS NOTED 02/13/23 JOB NO.: 22335 DRAWN BY

SEAL AND SIGNATURE:

CHECKED BY DRAWING NO.:

A-200.00

9 OF 36



2 REAR ELEVATION
Scale: 1/4" = 1'-0"



ELEVATION LEGEND:

- 1. ASPHALT ROOF SHINGLES
- 2. WOOD FASCIA BOARD
- 3. 5" O.G. GUTTER
- 4. HARDIE-PLANK SIDING
- 5. HARDIE-PLANK SIDING TRIM
- 6. STANDING SEAM METAL ROOFING
- 7. VINYL WINDOWS
- 8. ENTRY DOOR
- 9. WOOD POST
- 11. WOOD DECK W/ TREX DECKING PANELS
- 12. TREX RAILING
- 13. CONC. SLAB ON GRADE

10. CEMENTITIOUS STUCCO

14. CONC. SONOTUBE

BADALY

ENGINEERING DESIGN:

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

(914) 465-9010 BADALY.COM

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



E LA PUENTE ARC-CONSULTANT, LL

PATRICIA DE LA PUENTE PRINCIPAL CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM

PETER KLEIN , ASSOCIATES, INC ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

ELEVATION LEGEND:

1. ASPHALT ROOF SHINGLES

2. WOOD FASCIA BOARD

3. 5" O.G. GUTTER
4. HARDIE-PLANK SIDING

5. HARDIE-PLANK SIDING TRIM

6. STANDING SEAM METAL ROOFING

7. VINYL WINDOWS

8. ENTRY DOOR

9. WOOD POST

10. CEMENTITIOUS STUCCO
11. WOOD DECK W/ TREX DECKING PANELS

12. TREX RAILING

13. CONC. SLAB ON GRADE

14. CONC. SONOTUBE

SSU	IES:	
#	DATE	DESCRIPTION
EV	<u>'ISIONS:</u>	
#	DATE	DESCRIPTION
RC	DJECT TITLE:	
		0.555

NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TITLE:


SIDE BUILDING ELEVATIONS

SCALE: S
AS NOTED

DATE: 02/13/23

JOB NO.: 22335

DRAWN BY:



AK
CKED BY:
SB

DRAWING NO.:


A-201.00

10 OF 36



SIDE BUILDING ELEVATION

Scale: 1/4" = 1'-0"



ENGINEERING DESIGN:

BADALY ENGINEERING PLLC

(914) 465-9010 any alterations of these plans, unless done by oi UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCEI COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM PETER KLEIN , ASSOCIATES, IN

ARCHITECTS - BUILDERS - DEVELOPERS

CONSTRUCTION MANAGEMENT 44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

DATE DESCRIPTION # DATE DESCRIPTION

NEW SINGLE FAMILY RESIDENCE:

<u>1A PLUNKETT PL</u> WESTPORT, CT 10708

DRAWING TITLE:


PROJECT TITLE:

CROSS-SECTION

SEAL AND SIGNATURE: AS NOTED 02/13/23 JOB NO.: 22335 DRAWN BY HECKED B

DRAWING NO.:





BADALY

ENGINEERING DESIGN:

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

(914) 465-9010 BADALY.COM

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PATRICIA DE LA PUENTE PRINCIPAL CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM

PETER KLEIN, ASSOCIATES, INC ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

<u>ISS</u> L	JES:	
#	DATE	DESCRIPTION
<u>RE\</u>	/ISIONS:	
#	DATE	DESCRIPTION


NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TITLE:


PROJECT TITLE:

CROSS-SECTION



DRAWING NO.:

A-301.00




	1ST FLOOR WINDOW SCHEDULE (ANDERSEN 400 SERIES OR EQ'L)								1ST FLOOR DOOR SCHEDULE									
SYMBOL WDW #	REF	R/O	REMARKS	UNITS	LOCATION	HEADER	SYMBOL DOOR #	TYPE	SIZE	DOOR MTL	FRAME MTL	REMARKS		UNITS	LOCATION			
(101)	TW-21052	3'-0 1/8"X 5'-4 7/8'	DOUBLE HUNG	3	LIVING ROOM	2-2"X6"	1	EXTERIOR	6'-0"X7'-0"	WD	WD	DBL BI-PART		1	MAIN ENTRANCE			
	TW-21052	3'-0 1/8"X 5'-4 7/8'	DOUBLE HUNG	4	DINING ROOM	2-2"X6"	100	EXTERIOR	5'-0''X7'-0''	GL	WD	FRENCH DBL BI-PART		1	NOOK AREA/DECK			
	TW-21052	3'-0 1/8"X 5'-4 7/8'	DOUBLE HUNG	2	FAMILY ROOM	2-2"X6"	109	EXTERIOR	2'-6"X7'-0"	WD	WD	SWING SINGLE	RG	1	MUD ROOM			
	TW-21052	3'-0 1/8"X 5'-4 7/8'	DOUBLE HUNG EM/EG	1	GUEST ROOM	2-2"X6"		EXTERIOR	2'-6"X7'-0"	WD	WD	SWING SINGLE	LF	1	BSMNT STAIRS			
	TW-21052	3'-0 1/8"X 5'-4 7/8'	DOUBLE HUNG	5	FAMILY RM/DECK	2-2"X6"	(1)3	EXTERIOR	5'-0"X7'-0"	GL	WD	SLIDING	RG	1	OFFICE/PATIO			
(102)	TW-21042	3'-0 1/8"X 4'-4 7/8'	DOUBLE HUNG	3	KITCHEN	2-2"X6"	100	EXTERIOR	3'-0"X7'-0"	WD	WD	SWING SINGLE	LF	1	ENTRANCE			
(103)	P6030	6'-0 3/8"X 3'-0 1/2"	PICTURE TRANSOM	1	MAIN ENTRANCE	2-2"X10"	100	INTERIOR	2'-6"X7'-0"	WD	WD	SWING SINGLE	LF	1	OFFICE			
(104)	P6050	6'-0 3/8"X 5'-0 3/8"	PICTURE TRANSOM	1	MAIN ENTRANCE	2-2"X10"		INTERIOR	2'-6"X7'-0"	WD	WD	SWING SINGLE	LF	1	GUEST ROOM			
	1 0000	0 0 0,0 % 0 0 0,0	TICTORE TRAINSOW	'	MAIN ENTRANCE	2 2 110	_	INTERIOR	2'-6"X7'-0"	WD	WD	SWING SINGLE	RG	1	BATHROOM/GUEST RM			
(105)	TW2052	2'-2 1/8"X 5'-4 7/8'	DOUBLE HUNG	1	MUD ROOM	2-2"X4"		INTERIOR	2'-6"X7'-0"	WD	WD	SWING SINGLE	RG	1	BATHROOM/GUEST RM			
	TW2052	2'-2 1/8"X 5'-4 7/8'	DOUBLE HUNG	1	OFFICE	2-2"X4"		INTERIOR	2'-6"X7'-0"	WD	WD	SWING SINGLE	RG	1	POWDER ROOM			
(10)	TW18310	1'-10 1/8"X 4'-0 7/8'	DOUBLE HUNG	1	POWDER ROOM	2-2"X4"		INTERIOR	2'-6"X7'-0"	WD	WD	SWING SINGLE	LF	1	MUD ROOM			
				I	<u> </u>	<u> </u>	103	INTERIOR	2'-0"X7'-0"	WD	WD	SWING SINGLE	LF	1	PANTRY			

	2ND FLOOR WINDOW SCHEDULE (ANDERSEN 400 SERIES OR EQ'L)							2ND FLOOR DOOR SCHEDULE									
SYMBOL WDW #	REF	R/O	REMARKS	UNITS	LOCATION	HEADER	SYMBOL DOOR #	TYPE	SIZE	DOOR MTL	FRAME MTL	REMARKS		UNITS	LOCATION		
201	TW-21052	3'-0 1/8"X 5'-4 7/8	DOUBLE-HUNG EM/EG	1	MSTR BEDROOM	2-2"X6"	20)	EXTERIOR	5'-0''X7'-0''	GL	WD	FRENCH DBL BI-PART		1	MSTR BEDROOM		
	TW-21052	3'-0 1/8"X 5'-4 7/8'	DOUBLE-HUNG EM/EG	2	BEDROOM #3	2-2"X6"	202	INTERIOR	3'-0"X6'-8"	WD	WD	SWING SINGLE	LF	1	MSTR BEDROOM		
	TW-21052	3'-0 1/8"X 5'-4 7/8'	DOUBLE-HUNG EM/EG	2	BEDROOM #2	2-2"X6"	203	INTERIOR	3'-0"X6'-8"	WD	WD	POCKET SINGLE	LF	1	MSTR BATHROOM		
		,	·				204	INTERIOR	3'-0"X6'-8"	WD	WD	POCKET DBL BI-PART		1	LAUNDRY		
	TW-21052	3'-0 1/8"X 5'-4 7/8'	DOUBLE-HUNG EM/EG	2	BEDROOM #1	2-2"X6"	203	INTERIOR	2'-6"X6'-8"	WD	WD	SWING SINGLE	RG	1	BEDROOM #3		
	TW-21052	3'-0 1/8''X 5'-4 7/8'	DOUBLE-HUNG EM/EG	2	ENTER. AREA	2-2"X6"		INTERIOR	2'-6"X6'-8"	WD	WD	SWING SINGLE	LF	1	BATHRM #3		
202	TW-2652	2'-8 1/8"X 5'-4 7/8'	DOUBLE HUNG	2	MSTR BEDROOM	2-2"X6"		INTERIOR	2'-6"X6'-8"	WD	WD	SWING SINGLE	LF	1	BEDROOM #2		
203	TW-210310	3'-0 1/8"X 4'-0 7/8"	DOUBLE HUNG	1	MSTR BATHRM	2-2"X6"		INTERIOR	2'-6"X6'-8"	WD	WD	SWING SINGLE	RG	1	CLO BEDRM #2		
	TW-210310	3'-0 1/8"X 4'-0 7/8"	DOUBLE HUNG	1	BATHRM #3	2-2"X6"		INTERIOR	2'-6"X6'-8"	WD	WD	SWING SINGLE	LF	1	BATHRM #2		
			BOODEE HOIKE	·	DAIRM #3			INTERIOR	2'-6"X6'-8"	WD	WD	SWING SINGLE	LF	1	BEDROOM #1		
204	TW1852	1'-10 1/8"X 5'-4 7/8	DOUBLE HUNG	1	MSTR. WLK-IN CLO	2-2"X4"	203	INTERIOR	5'-0''X6'-8''	WD	WD	SWING DBL BI-PART		1	CLO BEDROOM #3		
	TW1852	1'-10 1/8"X 5'-4 7/8	DOUBLE HUNG	1	BEDROOM #3	2-2"X4"		INTERIOR	5'-0"X6'-8"	WD	WD	SWING DBL BI-PART		1	CLO BEDROOM #2		
203	P6050	6'-0 3/8"X 5'-0 3/8"	PICTURE	1	OPEN FOYER	2-2"X10"		INTERIOR	5'-0''X6'-8''	WD	WD	SWING DBL BI-PART		1	CLO BEDROOM #1		
200	TW18310	1'-10 1/8"X 4'-0 7/8	" DOUBLE HUNG	1	BATHRM #2	2-2"X4"		INTERIOR	5'-0"X6'-8"	WD	WD	SWING DBL BI-PART		1	LINEN CLO		
							200	INTERIOR	4'-0''X6'-8''	WD	WD	SWING DBL BI-PART		1	ENTERT. AREA		

Table of Tilt-Wash Scale ¹ /8" (3) = 1'-0"			dow Sizes	5						
Scale $\frac{1}{8}$ " (3) = 1'-0" Window Dimension	1'-9 ⁵ /8" (549)	2'-1 ⁵ /8" (651)	2'-5 ⁵ /8" (752)	2'-7 5/8"	2'-9 ⁵ /8" (854)	2'-11 ⁵ /8" (905)	3'-1 ⁵ /8" (956)	3'-5 ⁵ /8" (1057)	3'-9 ⁵ /8" (1159)	
Minimum Rough Opening	1-10 1/8" (562)	2'-2 1/8" (664)	2'-6 ¹ /8" (765)	2'-8 ¹ /8" (816)	2'-10 ½8" (867)	3'-0 ¹ /8" (917)	3'-2 ¹ / ₈ " (968)	3'-6 ¹ /8" (1070)	3'-10 ¹ /8" (1172)	
Unobstructed Glass (lower sash only)	15"	19" (483)	23" (584)	25" (635)	27" (686)	29" (737)	31" (787)	35" (889)	39" (991)	7
/8" (/8" () () ()		WIDTHS – 2	1 5/8" to 45 5	5/8"						Custom-size windows are available
3-0 //s" (937) 3-0 7/s" (937) 13 15/16" (354)	TW 18210	TW20210	TW 24210	TW 26210	TW 28210	TW 210210	TW 30210	TW 34210	TW 38210	in 1/8" (3) increments.
1140) (1038) 1140) (1038) 1140) (1038) 1140) (1038) 1715/16" (1515/16 456) (405)	TW 1832	TW 2032	TW 2432	TW 2632	TW 2832	TW 21032	TW 3032	TW 3432	TW 3832	
3'-8 //8" (1140) 3'-8 7/8" (1140) 17 15/16" (456)										Cottage or reverse cottage sash ratio available for heights shown below in all widths. CUSTOM WIDTHS — 21 5/s" to 45 5/s"
	TW1836	TW 2036	TW 2436	TW 2636	TW 2836	TW 21036	TW 3036	TW 3436	TW 3836	CUSTOM HEIGHTS — 48 ⁷ /s" to 76 ⁷ /s"
(1241) 4'-0 //8" 4'-0 7/8" (1241) 19 ⁷ /16" (495)										
	TW 18310	TW 20310	TW 24310	TW 26310	TW28310	TW 210310	TW 30310	TW 34310	TW38310	Cottage Reverse Cottage
(1343) 4'-4 7/8" 4'-4 7/8" (1343) 21 15/16" (557)										
	TW1842	TW 2042	TW 2442	TW 2642	TW 2842	TW 21042	TW 3042	TW 3442	TW 3842	
4'-8 //8" (1445) 4'-8 7/8" (1445) 23 7/16" (596)										
	TW 1846	TW 2046	TW 2446	TW 2646	TW 2846	TW 21046	TW 3046 ◊	TW 3446⁰	TW3846 ⁰	
5-0 /8" (1546) 5-0 7/8" (1546) 25 15/16" (659)										
	TW 18410	TW 20410	TW 24410	TW 26410	TW 28410	TW 210410 [◊]	TW30410 ⁰	TW34410 ⁰	TW38410 [◊]	
/8" 8) 8) (16"										
5-4 //8" (1648) 5-4 7/8" (1648) 27 15/16" (710)										
	TW 1852	TW 2052	TW 2452	TW2652	TW2852	TW21052°	TW 3052 ◊	TW3452♦	TW3852 ⁰	
5-8 /8" (1749) 5-8 7/8" (1749) 29 15/16" (760)										
	TW1856	TW 2056	TW 2456	TW 2656 	TW 2856♦	TW21056\$	TW 3056 ◊	TW 3456◊	TW3856 [◊]	
11) 11) 11) 10)										Size tables for windows with cottage or reverse cottage sash are available at andersenwindows.com/sizing.
6'-0 //8" (1851) 6'-0 7/8" (1851) 31 15/16" (811)										
	TW 18510	TW 20510	TW24510 ⁰	TW 26510⁰	TW 28510°	TW210510°	TW30510°	TW 34510	TW38510 ⁰	 "Window Dimension" always refers to outside frame-to-frame dimension. "Minimum Rough Opening" dimensions
6'-4 //8" (1953) 6'-4 7/8" (1953) 33 15/16" (862)										may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.

ANDERSEN® 400 SERIES WINDOW AND DOOR NFRC/ENERGY STAR® INFORMATION This document provides NFRC certified U-Factor, Solar Heat Gain Coefficient (SHGC) and Visible Transmittance (VT) values for Andersen® products along with the corresponding ENERGY STAR® Version 6.0 (2015) climate zones in which the product and glass type are certified. These products rated, certified and labeled y National Fenestration Rating Council® (NFRC) - a non-profit organization that provides fair, accurate and credible energy performance ratings for windows and doors. Many of our products meet the stringent energy efficiency certification criteria set by the U.S. Environmental Protection Agency and the U.S. Department of Energy. The certification criteria is based on the heat gain and loss of each product in various regions of the country. Check the Andersen product performance available at www.andersenwindows.com for units that are ENERGY STAR certified. United States ENERGY STAR® Canada ENERY STAR® Climate Zone Criteria Climate Zone Criteria ZONE 3 ZONE 2 South-Central = 0.28 ≥ 0.32 ≤ 0.25 Equivalent = 0.29 ≥ 0.37 Energy Performance = 0.30 ≥ 0.42 ≤ 0.30 ≤ 0.40 ≤ 0.30 ≤ 0.25 Southern ≤ 0.40 ≤ 0.25 ¹ Btu/h ft^로 또 ² Solar Heat Gain Coefficient * The effective date for the Northern Zone prescriptive and equivalent energy performance criteria for windows is January 1, 2016. For NFRC certified total unit performance for units with capillary breather tubes, please refer to the High Altittude information section for each unit. ¹U-Factor defines the amount of heat loss through the total unit in BTU/hr*ft 2*-F, metric in W/m2*K. The lower the value, the less the heat is lost through the entire product. ²Solar Heat Gain Coefficient (SHGC defines the fraction of solar radiation admitted through the glass both directly transmitted and absorbed and subsequently released inward. The lower the value, the less heat is transmitted through the product. ³Visible Transmittance (VT) measures how much light comes through a product (glass and frame). The higher the value, from 0 to 1, the more daylight the product lets in over the product's total unit area. Visible Transmittance is measured over the 380 to 760 nanometer portion of the solar spectrum. NFRC ratings are based on modeling by a third party agency as validated by an independent test lab in compliance with NFRC rpogram and procedural requirements. This data is accurate as of December 15, 2014. Due to ongoing product changes, updated test results or new industry standards or requirements, this data may changeover time. Due to variations in dealer and distributor inventory levels, products that were manufactured before December 15, 2014 that were designed, tested and labeled with different NFRC values may still be available. Check the labels on the product packaging to confirm NFRC values. Ratings are for sizes specified by NFRC for testing and certification. Ratings may vary depending on use of tempered glass, different grille options, glass for high altitude, etc. All marks where denoted are trademarks of their respective owners. © 2014 Andersen Corporation. All rights reserved. This information is for reference only. Performance varies by unit size and options selected. For specific unit performance information, please contact your dealer or Andersen Sales Representative.

BASEMENT DOOR SCHEDULE											
SYMBOL DOOR #	TYPE	SIZE DOOR FRAME MTL REMARKS					LOCATION				
	INTERIOR	3'-0"X7'-0"	WD	WD	SWING SINGLE; FPSC	1	UTILITY ROOM				
<u></u>	INTERIOR	3'-0"X7'-0"	WD	WD	SWING SINGLE	1	GARAGE				
8	INTERIOR	2'-0"X7'-0"	WD	WD	SWING SINGLE	1	CLOSET				
@	INTERIOR	5'-0"X7'-0"	WD	WD	DBL BI-PART	1	CLOSET				



ENGINEERING DESIGN:

BADALY ENGINEERING PLLC

(914) 465-9010 ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PETER KLEIN, ASSOCIATES, INC ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

DATE DESCRIPTION # DATE DESCRIPTION PROJECT TITLE:


NEW SINGLE FAMILY RESIDENCE:

<u>1A PLUNKETT PL</u> WESTPORT, CT 10708


DRAWING TITLE:


DOOR & WINDOW SCHEDULE

02/13/23 JOB NO.: 22335 DRAWN BY:




DRAWING NO.:






3/4" PORTLAND CEMENT

NITERIOR PARTITION AT FOUNDATION WALL





System No. W-L-2128

F Rating — 1 and 2 Hr (See Item 1) T Rating — 0 Hr

SYSTEM NO. F-C-2030

SYSTEM TESTED WITH A PRESSURE DIFFERENTIAL OF 2.5 PA BETWEEN THE EXPOSED AND THE UNEXPOSED SURFACES WITH THE HIGHER PRESSURE ON THE EXPOSED SIDE.

SYSTEM TESTED WITH A PRESSURE DIFFERENTIAL OF 2.5 PA SERVIEN THE EXPOSED AND THE UNEXPOSED SURFACES WITH THE HORPER PRESSURE ON THE EXPOSED SIDE.

1. FLOOR-CEILING ASSEMBLY — THE 1.0 R.2 HE FIRE FASTED SOLD OR TRUSSED LUMBER JOST FLOOR-CEILING SERVIEN THE PRESSURE ASSEMBLY MARE RESISTANCE DIRECTION. THE PRESSURE THE PROPER PROPERTY. THE PROPER PRESSURE THE PROPER PROPERTY. THE PROPER PRESSURE THE PROPER PRESSURE THE PROPER PROPERTY THE PROPER PRESSURE THE PROPER PRESSURE THE PROPER PRESSURE THE PROPER PROPERTY. THE PROPER PRESSURE THE PROPER PROPERTY. THE PROPERTY THE PR

110/4"N FIRESTOP COLLAR

* INDICATES SUCH PRODUCTS SHALL BEAR THE UL OR CUL CERTIFICATION MARK FOR JURISDICTIONS EMPLOYING THE UL OR CUL CERTIFICATION (SUCH AS CANADA), RESPECTIVELY.

SYSTEM NO. W-L-2128

1. WALL ASSEMBLY — THE 1 OR 2 HR FIRE-RATED GYPSUM WALLBOARD/STUD WALL ASSEMBLY SHALL BE CONSTRUCTED OF THE MATERIALS AND IN THE MANNER SPECIFIED IN THE INDIVIDUAL U300, U400, V400 OR W400 SERIES WALL AND PARTITION DESIGNS IN THE UL FIRE RESISTANCE DIRECTORY AND SHALL INCLUDE THE FOILDWING CONSTRUCTION FEATURES:

A. STUDS — WALL FRAMING MAY CONSIST OF EITHER WOOD STUDS OR STEEL CHANNEL STUDS. WOOD STUDS TO CONSIST OF NOM 2 BY 4 IN. (51 BY 102 MM) LUMBER SPACED 16 IN. (406 MM) OC. STEEL STUDS TO BE MIN 2-1/2 IN. (64 MM) WIDE AND SPACED MAX 24 IN. (610 MM) OC.

B. GYPSUM BOARD? — 5/8 IN. (16 MM) THICK, 4 FT (122 CM) WIDE WITH SQUARE OR TAPERED EDGES. THE GYPSUM WALLBOARD TYPE, THICKNESS, NUMBER OF LAYERS, FASTENER TYPE AND SHEET ORIENTATION SHALL BE AS SPECIFIED IN THE INDIVIDUAL WALL AND PARTITION DESIGN. MAX DIAM OF OPENING IS 3-1/2 IN. (89 MM). 2. METALLIC SLEEVE OPTIONAL — NOM 3-1/2 IN. (89 MM) (OR SMALLER) CYLINDRICAL SLEEVE FABRICATED FROM MIN 0.016 IN. THICK (28 GAUGE) GALV SHEET STEEL AND HAVING A MIN 1-1/4 IN. (32 MM) LAP SALONG LONGITUDINAL SEAM. LENGTH OF SLEEVE TO BE INSTALLED FLUSH WITH WALL SURFACES.

3. THROUGH PENETRANTS — ONE NONMETALLIC PIPE INSTALLED WITHIN THE FIRESTOP SYSTEM., PIPE MAY BE INSTALLED AT AN ANGE NOT GREATER THAN 45 DEGREES FROM PERPENDICULAR. PIPE TO BE RIGIDLY SUPPORTED ON BOTH SIDES OF WALL ASSEMBLY. THE SPACE BETWEEN PIPE AND PERIPHERY OF OPENING SHALL BE MIN 1/4 IN. (6 MM) TO MAX 11/16 IN. (17.5 MM). THE FOLLOWING TYPES AND SIZES OF NONMETALLIC PIPES A. POLYVINYL CHLORIDE (PVC) PIPE — NOM 2 IN. (51 MM) DIAM (OR SMALLER) SCHEDULE 40 PVC PIPE FOR USE IN CLOSED (PROCESS OR SUPPLY) OR VENTED (DRAIN, WASTE OR VENT) PIPING SYSTEMS.

B. CHLORINATED POLYVINYL CHLORIDE (CPVC) PIPE — NOM 2 IN. (51 MM) DIAM (OR SMALLER) SDR13.5 CPVC PIPE FOR USE IN CLOSED (PROCESS OR SUPPLY) PIPING SYSTEMS.

NGINEERING DESIGN:

BADALY ENGINEERING PLLC

914) 465-9010 ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY C UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCE COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PETER KLEIN , ASSOCIATES, IN ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573


DATE DESCRIPTION # DATE DESCRIPTION

NEW SINGLE FAMILY RESIDENCE:

<u>1A PLUNKETT PL</u> WESTPORT, CT 10708

DRAWING TITLE:

CONSTRUCTION <u>DETAILS</u>



02/13/23 JOB NO.: 22335 DRAWN BY: HECKED BY

DRAWING NO .:

RESIDENTIAL PLUMBING FIXTURES CLEARANCES & REQUIREMENTS

THE INSTALLATION OF FIXTURES SHALL CONFORM TO THE FOLLOWING:

1. FLOOR-OUTLET OR FLOOR-MOUNTED FIXTURES SHALL BE SECURED TO THE DRAINAGE CONNECTION AND TO THE FLOOR, WHERE SO DESIGNED, BY SCREWS, BOLTS, WASHERS, NUTS AND SIMILAR FASTENERS OF COPPER, COPPER ALLOY OR OTHER CORROSION-RESISTANT MATERIAL.

2. WALL-HUNG FIXTURES SHALL BE RIGIDLY SUPPORTED SO THAT STRAIN IS NOT TRANSMITTED TO THE PLUMBING SYSTEM.

3. WHERE FIXTURES COME IN CONTACT WITH WALLS AND FLOORS, THE CONTACT AREA SHALL BE WATER TIGHT.


4. PLUMBING FIXTURES SHALL BE USABLE.


5. WATER CLOSETS, LAVATORIES AND BIDETS. A WATER CLOSET, LAVATORY OR BIDET SHALL NOT BE SET CLOSER THAN 15 INCHES FROM ITS CENTER TO ANY SIDE WALL, PARTITION OR VANITY OR CLOSER THAN 30 INCHES CENTER-TO-CENTER BETWEEN ADJACENT FIXTURES. THERE SHALL BE A CLEARANCE OF NOT LESS THAN 21 INCHES IN FRONT OF A WATER CLOSET, LAVATORY OR BIDET TO ANY WALL, FIXTURE OR DOOR.

6. THE LOCATION OF PIPING, FIXTURES OR EQUIPMENT SHALL NOT INTERFERE WITH THE OPERATION OF WINDOWS OR DOORS.

7. IN FLOOD HAZARD AREAS AS ESTABLISHED BY TABLE R301.2(1), PLUMBING FIXTURES SHALL BE LOCATED OR INSTALLED IN ACCORDANCE WITH SECTION R322.1.6.

8. INTEGRAL FIXTURE-FITTING MOUNTING SURFACES ON MANUFACTURED PLUMBING FIXTURES OR PLUMBING FIXTURES CONSTRUCTED ON SITE, SHALL MEET THE DESIGN REQUIREMENTS OF ASME A112.19.2/CSA B45.1 OR ASME A112.19.3/CSA





-HORIZONTAL INSTALLED GFI OUTLETS, TYPICAL WALL --BULL NOSE BACKSPLASH -DRAWER CABINET BACKING PLYWOOD, TYP. **ADJUSTABLE** SHELF, TYP. BLOCKING TYP. FINISHED FLOOR -KICKBASE

-7'-0" DROPPED HEADER AT

KITCHEN PERIMETER WALLS

TYPICAL ELECTRICAL DEVICE LOCATION





THE SIGN OR SYMBOL SHALL SHALL CONSIST OF A CIRCLE SIX INCHES IN DIAMETER, WITH A STROKE WIDTH OF 1/2 INCH. THE BACKGROUND OF THE STICKER SHALL BE REFLECTIVE WHITE IN COLOR. THE CIRCLE CONTENTS SHALL BE REFLECTIVE RED IN COLOR, CONFORMING TO PANTONE MATCHING SYSTEM (PMS) #187.

THE SIGN OR SYMBOL SHALL BE OF STURDY, NON-FADING, WEATHER-RESISTANT MATERIAL; PROVIDED, HOWEVER, THAT A SIGN OR SYMBOL APPLIED DIRECTLY TO A DOOR SIDELIGHT MAY BE A PERMANENT NON-FADING STICKER OR DECAL.



ENGINEERED WOOD STICKER DETAIL Scale: 1" = 1'-0"





SHOWER CONSTRUCTION DETAIL

NGINEERING DESIGN:

BADALY ENGINEERING PLLC 914) 465-9010 ny alterations of these plans, unless done by c

UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209. DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCE COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PETER KLEIN , ASSOCIATES, IN ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

CEL. 914-6181847

PDLPARCHITECTURE@HOTMAIL.COM

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

DATE DESCRIPTION # DATE DESCRIPTION

NEW SINGLE FAMILY RESIDENCE: <u>1A PLUNKETT PL</u>

WESTPORT, CT 10708

DRAWING TITLE:

PROJECT TITLE:

CONSTRUCTION DETAILS

SEAL AND SIGNATURE: 02/13/23 22335 RAWN BY

16 OF 36

PLUMBING FIXTURE CLEARANCE Scale: 1/2" = 1'-0"

JACK STUD HEADER DETAIL
Scale: 1/4" = 1'-0"




LANDSCAPING SCHEDULE

MARK/PATTERN	QTY	BOTANICAL NAME	COMMON NAME	HABIT	SIZE AT PLANTING/MATURE
	5	THUJA OCCIDENTALIS ARBORVITAE		EVERGREEN	5'-0" HEIGHT./25'-0"
SHRUBS/PLANTS					
	-	SEASONAL FLOWERING	PLANTS/BUSHES	-	-
GROUND COVERING					
		GRASS			

LANDSCAPING NOTES:

THIS LANDSCAPING PLAN SHALL ONLY INCLUDE PLANT SPECIES THAT ARE APPROPRIATE BASED ON THE UNITED STATES DEPARTMENT OF AGRICULTURE'S PLANT HARDINESS ZONE MAP.

ALL LANDSCAPING SHALL LIVE FOR AT LEAST 3 YEARS AFTER THE ISSUANCE OF THE CERTIFICATE OF OCCUPANCY. ANY LANDSCAPING THAT DOES NOT MEET THIS REQUIREMENT SHALL BE REPLACED WITHIN TEN (10) DAYS OF NOTICING THAT THE LANDSCAPING IS INADEQUATE.



BADALY

NGINEERING DESIGN:

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

(914) 465-9010 BADALY.COM

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PATRICIA DE LA PUENTE
PRINCIPAL
CEL. 914-6181847
PDLPARCHITECTURE@HOTMAIL.COM

PETER KLEIN, ASSOCIATES, INC ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

DATE DESCRIPTION

REVISIONS:

DATE DESCRIPTION

PROJECT III F:

NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TITLE:

SITE LANDSCAPING PLAN

SCALE:

AS NOTED

DATE:

02/13/23

JOB NO.:

22335

DRAWN BY:

AK




DRAWING 1

C-100.00

17 OF 36

SITE LANDSCAPING PLAN
Scale: 1" = 20'-0"



EROSION CONTROL NOTES:

STABILIZE ENTIRE PILE

INSTALLATION NOTES:

OR COVERED.

FILTER CLOTH,

FILTER X, MIRAFI 100X

STABILINKA T140N OR APPROVED EQUAL

WOVEN WIRE FENCE (14 1/2 GA. MIN.,

6" MAX. MESH SPACING) WITH FILTER

24" AT TOP AND MID SECTION.

OR APPROVED EQUIVALENT.

IN THE SILT FENCE.

OR APPROVED EQUAL.

SETBACKS FROM TEMPORARY DRAINAGE SWALES.

4. UPON COMPLETION OF SOIL STOCKPILING, EACH PILE SHALL BE SURROUNDED

5. STOCKPILES REMAINING IN PLACE FOR MORE THAN A WEEK SHOULD BE SEEDED

AND MULCHED OR COVERED WITH GEOTEXTILE FABRIC SURROUNDED BY SILT FENCE.

FENCE

UNDISTURBED GROUND

WITH SILT FENCING OR STRAWBALES, THEN STABILIZED WITH VEGETABLE

6. SEE SPECIFICATIONS AND DETAILS FOR INSTALLATION OF SILT FENCE.

10' MAX. C. TO C.

WOVEN WIRE FENCE (MIN 14 1/2 GAUGE,

ELEVATION

<u>SECTION</u>

6" MAX. MESH SPACING)

CLOTH OVER.

CONSTRUCTION NOTES FOR FABRICATED SILT FENCE

1. 36" MIN. STEEL POSTS, EITHER T OR U TYPE OR 2" HARDWOOD POSTS, DRIVEN MIN. 16" INTO

2. WOVEN WIRE FENCE TO BE FASTENED SECURELY TO FENCE POSTS WITH WIRE TIES OR STAPLES.

3. FILTER CLOTH TO BE FASTENED SECURELY TO WOVEN WIRE FENCE WITH TIES SPACED EVERY

4. WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER THEY SHALL BE OVERLAPPED

BY SIX INCHES AND FOLDED. FILTER CLOTH SHALL BE EITHER FILTER X, MIRAFI 100X, STABLINKA T140N,

5. MAINTENANCE SHALL BE PERFORMED AS NEEDED AND MATERIAL REMOVED WHEN "BULGES" DEVELOP


6. CONTRACTOR MAY USE PREFABRICATED UNITS, AS MANUFACTURED BY GEOFAB, ENVIROFENCE,

EMBEDDED FILTER CLOTH MIN. 6" INTO GROUND

3. MAXIMUM SLOPE STOCKPILE SHALL BE 1 TO 2.

WITH VEGETABLE OR COVER

- 1. PRIOR TO THE START OF CONSTRUCTION EROSION CONTROL DEVICES SHALL BE IN PLACE AS SHOWN ON THESE PLANS.
- 2. FINAL GRADES SHALL BE ESTABLISHED AS SOON AS POSSIBLE AND TOP SOILED AND SEEDED TO PROVIDE A TURF, WHICH WILL STABILIZE SLOPES AND PREVENT EROSION.
- 3. SLOPES TO REMAIN OPEN FOR MORE THAN THREE WEEKS SHALL BE PROTECTED WITH TEMPORARY SEEDING OR STAKED NETTING.
- 4. EROSION CONTROL DEVICES SHALL BE INSPECTED AFTER EACH RAINFALL AND SHALL BE CLEANED, REPAIRED OR REPLACED AS NECESSARY.
- 5. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED IN ACCORDANCEN WITH "NYS STANDARDS AND SPECIFICATIONS FOR EROSION & SEDIMENT CONTROL".
- 6. THE CLEANING OF EXISTING DOWNSTREAM AREAS FROM ALL SILTATION AND CONSTRUCTION DEBRIS SHALL BE PERFORMED AS REQUIRED, AND UPON COMPLETION OF WORK.
- 7. THE ENGINEER MAY AT HIS DISCRETION REQUIRE ADDITIONAL EROSION CONTROL MEASURES THROUGHOUT CONSTRUCTION TO MITIGATE UNFORESEEN EROSION AND SILTATION.




CONSTRUCTION SPECIFICATIONS

- 1. STONE SIZE USE 2" STONE, OR RECLAIMED OR RECYCLED CONCRETE EQUIVALENT 2. LENGTH - NOT LESS THAN 50 FEET (EXCEPT ON A SINGLE RESIDENCE LOT WHERE A 30 FOOT MINIMUM LENGTH WOULD APPLY).
- 3. THICKNESS NOT LESS THAN SIX (6) INCHES. 4. WIDTH - TWELVE (12) FOOT MINIMUM. BUT NOT LESS THAN THE FULL WIDTH

PLAN VIEW - N.T.S.

- AT POINTS WHERE INGRESS OR EGRESS OCCURS. TWENTY-FOUR (24) FOOT IF SINGLE ENTRANCE TO SIGHT
- 5. FILTER CLOTH WILL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING
- 6. SURFACE WATER ALL SURFACE WATER FLOWING OR DIVERTED TOWARD CON-STRUCTION ENTRANCES SHALL BE PIPED ACROSS THE ENTRANCE. IF PIPING IS IMPRACTICAL. A MOUNTABLE BERM WITH 5:1 SLOPES WILL BE PERMITTED
- 7. MAINTENANCE THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHTS-OF-WAY, ALL SEDIMENT SPILLED, DROPPED, WASHED OR TRACKED ONTO PUBLIC RIGHTS-OF-WAY MUST BE REMOVED IMMEDIATELY
- 8. WHEN WASHING IS REQUITED, IT SHALL BE DONE ON A AREA STABILIZED WITH STONE AND WHICH DRAINS INTO AN APPROVED SEDIMENT TRAPPING DEVICE. 9. PERIODIC INSPECTION AND NEEDED MAINTENANCE SHALL BE PROVIDED AFTER EACH
- STABILIZED CONSTRUCTION ENTRANCE N.T.S.



- 1. BALES SHALL BE PLACED AT THE TOE OF THE SLOPE OR ON THE CONTOUR AND IN A ROW WITH END TIGHTLY ABUTTING IN ADJACENT BALES.
- 2. EACH BALE SHALL BE EMBEDDED IN THE SOIL A MINIMUM OF 4 INCHES AND PLACED SP THE BINDING ARE HORIZONTAL.
- 3. BALES SHALL BE SECURELY ANCHORED IN PLACE BY EITHER TWO STAKES OR REBARS DRIVEN THROUGH THE BALE. THE FIRST STAKE IN EACH BALE SHALL BE DRIVEN TOWARD THE PREVIOUSLY LAID BALE AT AN ANGEL TO FORCE THE BALES TOGETHER. STAKES SHALL BE DRIVEN FLUSH WITH THE BALE.
- 4. INSPECTION SHALL BE MADE FREQUENTLY AND REPAIR SHALL BE MADE PROMPTLY AS NEEDED.
- 5. BALES SHALL BE REMOVED WHEN THEY SERVED THEIR USEFULNESS SO AS NOT TO BLOCK OR IMPEDE STORM FLOW OR DRAINAGE.



NGINEERING DESIGN: BADALY ENGINEERING PLLC

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY C UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCEI COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT DE LA PUENTE ARC-CONSULTANT, LLC PATRICIA DE LA PUENTE

PETER KLEIN, ASSOCIATES, IN ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

CEL. 914-6181847

PDLPARCHITECTURE@HOTMAIL.COM

44 WINDING WOOD ROAD

RYE BROOK, NEW YORK 10573

DATE DESCRIPTION # DATE DESCRIPTION PROJECT TITLE:

NEW SINGLE FAMILY RESIDENCE: **1A PLUNKETT PL**


WESTPORT, CT 10708


DRAWING TITLE:


EROSION CONTROL <u>PLAN</u>

SEAL AND SIGNATURE: AS NOTED 02/13/23 JOB NO.: 22335 DRAWN BY CHECKED BY

DRAWING NO .:








PAVERS DETAIL
Scale: 1 1/2" = 1'-0"

2 PAVERS DETAIL WITH BELGIAN BLOCK CURB Scale: 1 1/2" = 1'-0"

3 ASPHALT DRIVEWAY DETAIL
Scale: 1 1/2" = 1'-0"



SEGMENTAL BLOCK RETAINING WALL DETAIL
Scale: 1/2" = 1'-0"

ENGINEERING DESIGN:

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

(914) 465-9010 ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PETER KLEIN , ASSOCIATES, IN ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

DATE DESCRIPTION # DATE DESCRIPTION

PROJECT TITLE:


NEW SINGLE FAMILY RESIDENCE:

<u>1A PLUNKETT PL</u> WESTPORT, CT 10708

DRAWING TITLE:

SITE DETAILS

SEAL AND SIGNATURE: 02/13/23 22335 DRAWN BY CHECKED BY



DRAWING NO.:

PLAN LEGEND

KX KITCHEN EXHAUST

BX BATHROOM EXHUAST

VERTICAL HVAC DUCT

VERTICAL HVAC DUCT

STARTING AT CEILING

FLOOR SUPPLY REGISTOR

CEILING SUPPLY REGISTOR

SIDEWALL SUPPLY REGISTOR

SIDEWALL SUPPLY REGISTOR


CEILING RETURN REGISTOR

BATHROOM EXHAUST

S.A.

{20}

EXHAUST (20 CFM)



BASEMENT MECHANICAL PLAN

| Scale: 1/4" = 1'-0"



NGINEERING DESIGN

LAW ARTICLE 145, SECTION 7209.

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

(914) 465-9010 BADALY.

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PATRICIA DE LA PUENTE PRINCIPAL CEL. 914-6181847

PETER KLEIN , ASSOCIATES, INC ARCHITECTS - BUILDERS - DEVELOPERS

PDLPARCHITECTURE@HOTMAIL.COM

construction management
44 winding wood road

RYE BROOK , NEW YORK 10573

<u>ISS</u> L	JES:	
#	DATE	DESCRIPTION
REV	/ISIONS:	
#	DATE	DESCRIPTION

PROJECT TITLE:

NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TITLE:

<u>BASEMENT</u> <u>MECHANICAL PLAN</u>

SCALE: SEAL AND SIGNATURE:
AS NOTED

DATE: 02/13/23 JOB NO.: 22335 DRAWN BY: AK




DRAWING NO.:

CHECKED BY

M-100.00

SHEET NO.: 20 OF 36



BADALY

ENGINEERING DESIG


BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

4) 465-9010 BADALY.C

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



DE LA PUENTE ARC-CONSULTANT, LLC

PATRICIA DE LA PUENTE PRINCIPAL CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM

PETER KLEIN, ASSOCIATES, INC ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TITLE:

<u>FIRST FLOOR</u> MECHANICAL PLAN

LE: SEAL AND SIGN

AS NOTED

DATE:
02/13/23

JOB NO.:
22335

DRAWN BY:



20

M-101.00

SHEET NO.: 21 OF 36

PLAN LEGEND

KX KITCHEN EXHAUST

BX BATHROOM EXHUAST

VERTICAL HVAC DUCT

VERTICAL HVAC DUCT

STARTING AT CEILING

FLOOR SUPPLY REGISTOR

CEILING SUPPLY REGISTOR

SIDEWALL SUPPLY REGISTOR

SIDEWALL SUPPLY REGISTOR


CEILING RETURN REGISTOR

BATHROOM EXHAUST

S.A.

SUPPLY (20 CFM)

EXHAUST (20 CFM)



SECOND FLOOR MECHANICAL PLAN
Scale: 1/4" = 1'-0"

BADALY

NGINEERING DESIGN:

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

(914) 465-9010 BADALY.COM

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION

LAW ARTICLE 145, SÉCTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM

CONSULTANT

BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.



DE LA PUENTE ARC-CO

PATRICIA DE LA PUENTE PRINCIPAL CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM

PETER KLEIN , ASSOCIATES, INC ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

<u>ISS</u> I	JES:	
#	DATE	DESCRIPTION
RE\	/ISIONS:	
#	DATE	DESCRIPTION

NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TI

PROJECT TITLE:

SECOND FLOOR MECHANICAL PLAN

AS NOTED

DATE:
02/13/23

JOB NO.:
22335





CHECKED BY: SB

M-102.00

SHEET NO.: 22 OF 36

PLAN LEGEND





ATTIC MECHANICAL PLAN
Scale: 1/4" = 1'-0"

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION

LAW ARTICLE 145, SECTION 7209. DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PATRICIA DE LA PUENTE PRINCIPAL CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM

Peter Klein , associates, inc ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

ISSU	JES:	
#	DATE	DESCRIPTION
REV	<u> (ISIONS:</u>	
#	DATE	DESCRIPTION


NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TITLE:

PROJECT TITLE:

ATTIC MECHANICAL <u>PLAN</u>




M-103.00

SHEET NO.: 23 OF 36

FURNACE: 59MN7A060-14

Infinity® Modulating 4-Way Multipoise Condensing Gas Furnace (Carrier) turn to the experts Series 100

Product Data



The 59MN7A Multipoise Variable-Capacity Condensing Gas Furnace features the modulating Infinity® System. The innovative modulating gas valve is at the heart of this furnace's quiet operation, along with the variable-speed ECM blower motor and variable-speed inducer motor. This furnace also provides 3.5 times tighter temperature control than single stage furnaces. With an Annual Fuel Utilization Efficiency (AFUE) up to 97.4%, this Infinity gas furnace provides exceptional savings over standard furnaces as well. This Infinity Gas Furnace also features 4-way multipoise installation flexibility. The 59MN7A can be vented as a direct vent/two-pipe furnace or as an optional ventilated combustion air application. A Carrier Infinity® Control and an Infinity Air Conditioner or Heat Pump can be used to form a complete Infinity System. All units meet California Air Quality Management District emission requirements. All sizes are design

STANDARD FEATURES

- Our quietest furnace. Compare for yourself at
- HVACpartners.com • Supports single- and multiple-zone Infinity systems • Ideal height 35" (889 mm) cabinet: short enough for taller
- coils,but still allows enough room for service • Infinity Features—match with the Infinity Control for Infinity



INFINITY SYSTEM

Carrier's 24VNA0 with Greenspeed[™] Intelligence is a variable

speed cooling product providing up to 20.5 SEER cooling

efficiency. Lower speed operation, when needed in cooling, for

This product has been designed and manufactured to meet Energy

Star® criteria for energy efficiency when matched with appropriate

coil components. Refer to the combination ratings in the Product

NOTE: Ratings contained in this document are subject to

change at any time. Always refer to the AHRI directory

(www.ahridirectory.org) for the most up-to-date ratings

Data for system combinations that meet Energy Star® guidelines.

enhanced comfort and dehumidification.

information.





installation.†



• Integral part of the Ideal Humidity System® Technology

• SmartEvap[™] technology helps control humidity levels in the

home when used with a compatible humidity control system

• ComfortFan[™] technology allows control of continuous fan

• 4-way multipoise design for upflow, downflow or horizontal

installations, with unique vent elbow and optional through-

• Variable-Speed blower and inducer motors, modulating gas

• Self-diagnostics and extended diagnostic data through the

• Adjustable blower speed for cooling, continuous fan, and

• Stainless-steel condensing secondary heat exchanger

• Factory-configured ready for upflow applications

• Fully-insulated casing including blower section

• Installation flexibility: sidewall or vertical vent

original purchaser upon timely registration.

* For owner occupied, residential applications.

tion will receive registered limited warranty benefits.

through the Retail Credit Program

Advanced Product Monitor (APM) accessory or Infinity User

• Convenient Electronic Air Cleaner and Humidifier connections

• Residential installations may be eligible for consumer financing

LIMITED WARRANTY*

• 10 year parts and lifetime heat exchanger limited warranty to the

• Limited warranty period is five years for parts and twenty years

†Jurisdictions where warranty benefits cannot be conditioned on registra-

for the heat exchanger if not registered within 90 days of

Direct-vent/sealed combustion or ventilated combustion air

• Silicon Nitride Power Heat™ Hot Surface Igniter

speed from a compatible thermostat

• External Media Filter Cabinet included

the-cabinet downflow venting capability

• Aluminized-steel primary heat exchanger

• Propane convertible (See Accessory list).



(BTUH) aximum Heat 59,000 117,000 rmediate Heat 76,000 linimum Heat (BTUH) 47,000 AFUE % (ICS 97.4 97.2 35 - 65 (19-36) 45 - 75 (25-41) Maximum Heat (21-38) (25-41)Certified Temperature Intermediate Heat Rise Range °F (°C) (27-44)(27-44)(27-44)Minimum Heat (19-36) (19-36) (19-36) (19-36) Airflow Capacity and Blower Data 100-20 120-22 Pressure (in. w.c.) Maximum Heat 1815 Airflow Delivery Minimum Heat @ Rated ESP (CFM) Cooling 2185 400 CFM/ton Cooling Capacity (tons) @ 400, 350 CFM/ton 350 CFM/ton Direct-Drive Motor Type Direct-Drive Motor HP Motor Full Load Amps Speed Selections Variable (Communicatin 11 x 8 | 11 x 10 | 11 x 11 Blower Wheel Dia. X Width Factory Supplied Media Cabinet Air Filtration System Filter Used for Certified Watt Data GAWF1306UFR KGAWF1306UFR KGAWF1406UFR KGAWF1506UFR Electrical Data Volts-Hertz-Phase Operating Voltage Range Min-Max Maximum Input Amps Unit Ampacity Amps Minimum Wire Size AWG Maximum Wire Length (8.8) (8.8) @ Minimum Wire Size Maximum Fuse/Ckt Bkr (Time-Delay Type Recommended) Amps Transformer Capacity (24vac output) External Control Power 27.9 VA Cooling Controls 060-14 080-14 100-20 120-22 Gas Connection Size Burners (Monoport) Manufacturer Minimum Inlet Gas 4.5 pressure (in. W.C.) Gas Valve (Redundant) 13.6 pressure (in. W.C.) KGANP5201VSP Gas Conversion Kit - Natural to Propane Gas Conversion Kit - Propane to Natural KGAPN4401VSP Manufactured (Mobile) Home Kit not approved for MH use Silicon Nitride Adjustable: 90, 120, 150, 180 seconds Heating Blower Control (Heating Off-Delay) Cooling Blower Control (Time Delay Relay) Infinity; Infinity Zoning Thermostat Connections W2, Y1, DHUM, G, COM 24V, W/W1, Y/Y2, R EAC (115vac); HUM (24vac); 1-stg AC (via Y/Y2

BATHROOM EXHAUST: PANASONIC FV-0911RF1

of the original purchase.

Architectural Specifications

Ventilation fan shall be ceiling mount, ENERGY

from 80/110 CFM and no more than 0.3/0.8

sone as certified by the Home Ventilating

Institute (HVI) at 0.1 static pressure in inches

rated with efficiency of no less than 3.8/4.2

(3" if using the included duct adapter). The motor

rating shall be 120v/60Hz. Housing material shall

be no less than 26 gauge galvanized steel with

rust proof epoxy and polyester resin coating.

Fan shall be UL and cUL listed for tub/shower

used to comply with ASHRAE 62.2, LEED,

ENERGY STAR® IAP, EarthCraft, California

Title-24, and WA Ventilation Code.

shall be totally enclosed, four pole condenser

type engineered to run continuously. Power

WhisperFit EZ

Specification Submittal Data / Panasonic Ventilation Fan

Ventilating fan shall be low sone ceiling mount rated for continuous operation. Fan shall be ENERGY STAR® rated and certified by the

Home Ventilating Institute (HVI). Evaluated by the Underwriters Laboratories and conform to both UL and cUL standards.


Motor/Blower: Four-pole totally enclosed condenser AC motor rated for continuous use. Fan ventilation rates shall be manually

adjustable for 80 or 110 CFM. • Power Rating shall be 120 volts and 60 Hz. • Fan shall be UL and cUL listed for tub/shower enclosure when GFCI protected. • Motor equipped with thermal cutoff fuse. Removable, permanently lubricated, plug-in

• Rust proof epoxy and polyester resin coating, 26 gauge galvanized steel body. • 4" diameter duct with optional 3" adapter • Built in backdraft damper.

 Attractive design using Poly Pro material. Attaches directly to housing with torsion springs.

FV-08-11VF5



See Following Page for Performance Curves

FV-08-11VF5

0	MA:		110 CFN	/I Setting	1	80 CFM Setting				
Specifications	:: WhisperFit® EZ FV-08-11VF5	4" I	Duct	3" Duct		4" Duct		3" Duct		
	Static Pressure in inches w.g.	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.2	
	Air Volume (CFM)	110	104	100	88	80	73	70	61	
	Noise (sones)	0.8	1.2	1.3	1.5	0.3	0.6	0.5	1.	
V	Power Consumption (Watts)	26.5	26.4	26.4	25.9	21.1	20.7	20.9	20.	
Ventilation Fan Characteristics	Energy Efficiency (CFM/Watt)	4.2	4.0	3.9	3.5	3.8	3.5	3.5	3.:	
(HVI Certified Data)	Speed (RPM)	961	1179	1215	1369	848	1123	1005	123	
(iiii Goranica Bata)	Current (amps)	0.23	0.23	0.22	0.22	0.18	0.17	0.17	0.1	
	MAX. Current (amps)	0	.23	0.23		0.18		0.18		
	Power Rating (V/Hz)	12	0/60	120/60		120/60		120/60		
	ENERGY STAR rated	Y	YES		YES		YES		YES	

For complete Installation Instructions visit us.panasonic.com/ventfans

• Articulating and expandable extension bracket enclosure when GFCI protected. Fan can be

Model	Quantity	Comments	Project:
			Location:
			Architect:
			Engineer:
			Contractor:
			Submitted by:
			Date:

Panasonic Eco Solutions North America Eco Products Division

Newark, NJ 07102

us.panasonic.com/ventfan HVI CERTIFIED CUL US FINERRY STAR

Panasonic

COIL: CARRIER 24VNA036

Infinity® Variable Speed Air Conditioner with Greenspeed™ Intelligence 2 to 5 Nominal Tons (Carrier) turn to the experts

Advance Product Data

INDUSTRY LEADING FEATURES / BENEFITS

Energy Efficiency

• Up to 20.5 SEER / 15.5 EER Microtube Technology[™] refrigeration system Indoor air quality accessories available

• Sound level as low as 58 dBA in low speed

Comfort • Variable speed scroll compressor with capacity range from 40-100%

• Air cooled Inverter variable speed drive System requires Infinity® wall control (SYSTXCCITW01-A, SYSTXCCITC01-A, SYSTXCCITC01-B or newer)

• Energy Tracking capability with the Infinity wall control

w/software version 13 or later (Energy Tracking has the ability to monitor and estimate the energy consumption of your Infinity system.) Reliability

• Non-ozone depleting Puron® refrigerant Front-seating service valves

• Infinity Intelligence monitors critical system parameters High pressure switch • Suction pressure transducer TXV for cooling

• Filter drier (field installed) · Internal crankcase heater standard Flexibility and installation: • 2 control wires to outdoor unit

• Minimum and maximum airflow adjustments

WeatherArmor Ultra[™] protection package: Solid, Durable sheet metal construction

 Steel louver coil guard • Baked-on, complete outer coverage, powder paint **Applications**

• Long-line - up to 250 feet (76.2 m) total equivalent length, up to 200 feet (60.96 m) condenser above evaporator, or up to 80 ft. (24.38 m) evaporator above condenser (See Longline Guide for

MIN/MAX AIRFLOW TABLES

The indoor airflow delivered by this system varies significantly the system will deliver full capacity at all outdoor temperatures. based on outdoor temperature, indoor unit combination, and Minimum and maximum airflows can be adjusted from these system demand. The airflows on these tables are for duct design numbers in the Infinity wall control air conditioner Setup screen. considerations. Duct systems capable of these ranges will ensure

Size	wax Capacity	wiin Capacity	(Delium of Zoning)
24	726	651	398
36	1168	651	398
48	1394	1186	693
60	1650	1186	693
	Cooling - Eff	iciency Mode	
Size	Max Ca	apacity	Min Capacity
24	94	19	830
36	13	34	830
48	15	93	1355
60	18	85	1355

UNIT SIZE SERIES	24-30	36-30	48-30	60-30
Operating Weight lb (kg)	315 (143)	315 (143)	324 (147)	324 (147)
Shipping Weight lb (kg)	351 (159)	351 (159)	362 (164)	362 (164)
Compressor Type	()		eed Scroll	(,
REFRIGERANT			(R-410A)	
Control		TXV (Puron®	Hard Shutoff)	
Charge Ib (kg)	12.7 (5.76)	12.7 (5.76)	14.0 (6.35)	14.0 (6.35)
COND FAN		Forward Swept Prope	ller Type, Direct Drive	•
Air Discharge		Ver	ical	
Air Qty (CFM)	2700	4269	4350	5000
Motor HP	1/3	1/3	1/3	1/3
Motor RPM	500-900	500-900	500-900	500-900
COND COIL				
Face Area (Sq ft)	30.25	30.25	30.25	30.25
Fins per In.	20	20	20	20
Rows	2	2	2	2
Circuits	8	8	8	8
VALVE CONNECT. (In. ID)				
Vapor	7/8	7/8	7/8	7/8
Liquid	<u> </u>	3	8	
REFRIGERANT TUBES (In. OD)				
Rated Vapor*	7/8	7/8	1 – 1/8	1-1/8

* Units are rated with 25 ft (7.6 m) of lineset length. See Vapor Like Sizing and Cooling Capacity Loss table when using other sizes and lengths of lineset. Note: See unit Installation Instruction for proper installation.

THERMOSTAT: NEST LEARNING THERMOSTAT

SPEC SHEET

Nest Learning Thermostat Programs itself. Then pays for itself.



Meet the Nest Learning Thermostat.

It learns what temperatures you like, turns itself down when you're away and connects to your phone. It has a big, sharp display. And it's proven to help save energy. In independent studies, the Nest Thermostat saved an average of 10% to 12% on heating bills and 15% on cooling bills. We've estimated average savings of \$131 to \$145 a year.

How does it work?

Palo Alto, CA 94304

Auto-Schedule
No more confusing programming.

It learns the temperatures you like and programs itself. Connect the Nest Thermostat to Wi-Fi to

change the temperature from your phone, tablet or laptop. Nest Leaf You'll see the Leaf when you choose a temperature that saves energy. It guides you in

the right direction.

Nest learns how your home warms up and keeps an eye on the weather to get you the temperature you want when you want it.

Home/Away Assist
The Nest Thermostat automatically turns itself down when you're away to avoid heating

> See when heating and cooling were on and what affected your energy use.

or cooling an empty home.

Get an alert on your phone or tablet if your home gets dangerously hot or cold.

the time, temperature or weather.

When the Nest Thermostat spots you across the room, it lights up beautifully to show you

1-855-VIP-NEST



BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY O

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION

CONSULTANT



PETER KLEIN , ASSOCIATES, INC ARCHITECTS - BUILDERS - DEVELOPERS

CONSTRUCTION MANAGEMENT

CEL. 914-6181847

PDLPARCHITECTURE@HOTMAIL.COM

44 WINDING WOOD ROAD

RYE BROOK, NEW YORK 10573

DATE DESCRIPTION REVISIONS: # DATE DESCRIPTION

NEW SINGLE FAMILY RESIDENCE:


<u>1A PLUNKETT PL</u> WESTPORT, CT 10708

DRAWING TITLE:

PROJECT TITLE:

<u>SPECIFICATIONS</u>

AS NOTED 02/13/23 JOB NO.: 22335 DRAWN BY



SB DRAWING NO.:

CHECKED B,

BROAN B150E75NT ERV





Introducing the industry's most advanced residential fresh air system, created to offer a universal platform specifically designed and improved to make contractors life easier and more profitable while delivering constant superior air quality.

- Thanks to the Virtuo Air Technology[™], the airflow calibration and auto-balancing are achieved quickly and

 • Corrosion resistant galvanized steel door and body maintained throughout the life of the product
- Select the desired CFM (from 35 to 136 CFM) using the very first integrated LCD screen. The airflow is then set

 • Virtuo constant airflow and auto-balancing device up automatically
- Integrated electronic airflow measurement device with
 Motorized dampers (no additional backdraft dampers
- real time LCD Integrated diagnostic tool
- Equipped with PMSM ECM motors for a very low power
 6' power cord
- consumption Suspended installation (chains included)
- Wall-mount installation (universal brackets included)
- installation with 2 brackets installation with 4 brackets







for more information.

Fresh Air Systems - 130 CFM



Top ports: B150E75NT Side ports: B150E75NS

> 35 to 136 CFM @ 0.2 in. w.g. 35 to 127 CFM @ 0.4 in. w.g.









Visit www.broan-nutone.com for complete warranty text.

Unit Description

- SRE of 75% at 32°F and 60% at 14°F (65 CFM)
- Ports size: 5"
- Negative pressure defrost (exhaust defrost)
- One-piece molded insulation shell, no air leakage (expanded polystyrene; UL 94 HF-1 certified)
- (patent pending)
- required) No drain required
- Unit electrical characteristics: 120 volts, 60 Hz, 2.5 A, 163 W



There are 4 optional main controls and 2 optional auxiliary controls available. Refer to Wall Control specification sheet Options

PRODUCT SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

 Polypropylene crossflow core with polymeric membrane and aluminum covers, impact resistant, non washable


• Dimensions: 12" x 12" x 9" (30.5 cm x 30.5 cm x 23 cm)

 MERV 8 grade washable standard filter (included) • Optional MERV13 grade filter part no. V24285

- Complete line of registers and diffusers
- Compatible with the Tandem transition (part no. VTYIK1) (for units producing up to 110 CFM only)

NOTE: EQUIPMENT SIZING CACULATED IN ACCORDANCE WITH ANSI/ASHRAE/ACCA STANDARD 183

	HEATING & COOLING EQUIPMENT SCHEDULE														
QUANITY	TAG	MAKE	MODEL	DESCRIPTION	LOCATION	HEATING CAPACITY	PROPOSED HEATING EFFICIENCY	REQUIRED HEATING EFFICIENCY	COOLING CAPACITY	PROPOSED COOLING EFFICIENCY	REQUIRED COOLING EFFICIENCY				
2	F	DAIKIN	59MN7A060	FURNACE	BASEMENT & ATTIC	60.0 KBTU/H	97.4% AFUE	80.0% AFUE	-	-	-				
2	С	DAIKIN	24VNA036	COIL	BASEMENT & ATTIC	-	-	-	36.0 KBTU/H	18.0 SEER	13.0 SEER				



ATTIC UNIT CLEARANCE DETAILS



LAW ARTICLE 145, SECTION 7209.

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PATRICIA DE LA PUENTE CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM

peter klein , associates, inc ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

ISSU	JES:	
#	DATE	DESCRIPTION
<u>RE\</u>	/ISIONS:	
#	DATE	DESCRIPTION

PROJECT TITLE:

NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

RAW SPECIFICATIONS, **MECHANICAL** <u>EQUIPMENT</u> SCHEDULE, AND **DETAILS**

as noted 22335



CHECKED BY

M-201.00

SHEET NO.: 25 OF 36

BASEMENT AND FIRST FLOOR HEAT LOSS

	Project	BASEMENT AND F	IRST FLOOR	Design State & 0		Connecticut	J, 8TH EDIT	Bridgeport AP		4	
		r Design Heating db	72	@ Outdoor (Winter) 99%		7		HTD	65	~	
	Indoo	Design Cooling db	75	@ Outdoor (Summer) 1%		95		CTD	20	N	CN
	Indoor	Design Cooling RH	50%	Grains Differe	ence	36		Daily Range	Medium		
		Latitude	41	Eleva	tion	10		ACF	1.000		(Load
		Glass Direction		Construction Detail			Heating HTM	Cooling HTM	Net Area	Heating BTUH	Cooling BTUH
6A \	Windows		ANDERSEN W				17.55	16.00	32	562	512
Į.	& Glass	S	ANDERSEN W				17.55	19.00	66	1158	1254
	Doors - -	E/W	ANDERSEN W	/INDOWS			17.55	35.00	245	4300	8575
	-										
6B \$	Skylights										
_ [
7	Wood &		11D, Wood Cor				25.35	12.09	105	2662	1269
	Metal Doors	b c	11J, Metal Door	r, Fiberglass Core			39.00	18.60			
8	Above Grade Wa		PLUNKETT PL	ACE WALL			2.86	1.17	4846	13859	5650
		b									
		C									
		d e									
h	Partition Walls	f					1				
		g									
9	Below Grade Wal	ls a b	PLUNKETT BA	SEMENT			2.80		1987	5553	
10	Ceilings	a b	18A-0 Ceiling B	Below Joists, R-49 Insulation			1.76	0.73			
		С									
	Partition Ceilings	d e									
11 I	Passive Floors	а									
		b									ļ
	Exposed Floors	C 4)									ļ
_	Slab (Perimeter F Basement Floor	t.) d e						-			1
-	Partition Floors	e f									
_ [g									
12	Infiltration	Envelope Leakage	Tight	Heated & Cooled		3195	Above Grad	e = Cu Et	30304	3611	556
14	ווווווומנוטוו	No. of Fireplaces		Floor Area = Sq. Ft.			ADOVE GI 80			3011	
13	Internal Gains		Appliana 400	Number of Bedroom	ms	5		Occupants	6		1380
	Sub Totals		Appliance - 120	UDIUH						31705	1200 20396
<u> </u>	GUD I ULAIS		7F-Ducts in Co	anditioned Space				ı		31700	20390
15 I	Duct Loss & Gair	1	R-Value = 6	Leakage Class .12/.24 quare Feet of Surface or Default = 1		Supply	1	Return	1		
16 V	Ventilation	Combustion Air From (Vater H		No.	ne	ı		
	Blower Heat Gain			performance data has no blower hea			, , , , , ,	-		Ī	1707
	Total Sensible Lo									31705	22103
								on load for coolin	ng		618
		BADAL	Y ENGINEERIN	IG	1		Latent load for	occupants			1200
			LSON PLACE			04	Latent load for	Small	Medium	Large	
		MOUNT \	LSON PLACE /ERNON, NY 10 4) 465-9010	0550		21	plants	Small duct in unconditi		Large	

BASEMENT AND FIRST FLOOR HEAT LOSS SUMMARY

		IVIAIVOAL JOAI	• SUMMARY RE	- OKI		
			Mfg. Equipi	ment Sensible Heat Ratio	0.75	ACCA
Project	BASEMENT AND FIRST FLOOR			de Entry for Design CFM		Manual D
	Room Name	HEAT LOSS	HTG CFM	HEAT GAIN	CLG CFM	CFM
	BASEMENT	6100	192	1456	71	192
	DINING ROOM	4098	129	3357	165	165
	KITCHEN	3563	112	3285	161	161
	FOYER	2060	65	859	42	65
	FAMILY ROOM	4686	148	4358	214	214
	MUD ROOM	1863	59	1014	50	59
	BATHROOM 1	553	17	286	14	17
	BATHROOM 2	1264	40	541	27	40
	GUEST ROOM	1072	34	586	29	34
	OFFICE	2615	82	1848	91	91
	HALL	1043	33	434	21	33
	LIVING ROOM	2789	88	2372	116	116
Ro	om Envelope Totals	31705	1000	20396	1000	
Total Area	Construction Components	HEAT L	.oss	HEAT GA	AIN	
343	Windows & Glass Doors	6020	18.99%	10341	46.79%	
	Skylights					1
105	Wood & Metal Doors	2662	8.40%	1269	5.74%	1
4846	Above Grade Walls	13859	43.71%	5650	25.56%	1
	Partition Walls					
1987	Below Grade Walls	5553	17.52%			
	Ceilings					
	Partition Ceilings					
	Passive Floors					
	Exposed Floors					
	Slab Floors					
	Basement Floors					
	Partition Floors					
	Infiltration	3611	11.39%	556	2.51%	
	Internal Gains			2580	11.67%	
	Duct Loss & Gain]
	Ventilation					
	Blower Heat Gain			1707	7.72%	
	Total Sensible	31705	100.00%	22103	100.00%	
	Total Latent			1818		1
	Total Cooling Load			23921		

SECOND FLOOR HEAT LOSS SUMMARY

Project	SEC	OND FL		1AE ◆ ABRIDGED VERSIO Design State & City	Connecticut		Bridgeport AP			
	or Design Heat			@ Outdoor (Winter) 99% db	7		HTD	65		
Indo	or Design Coo	ing db	75	@ Outdoor (Summer) 1% db	95		CTD	20	N	
Indo	or Design Cool	ing RH	50%	Grains Difference	36		Daily Range	Medium		
	L	atitude	41	Elevation	10		ACF	1.000	Block	Load
	Glass					Heating	Cooling	Net	Heating	Cooling
	Directio	n		Construction Detail		нтм	нтм	Area	BTUH	BTUH
A Windows	N		ANDERSEN WIN			17.55	16.00	33	579	528
& Glass	S		ANDERSEN WIN			17.55	19.00	39	684	741
Doors	E/W		ANDERSEN WIN	IDOWS		17.55	35.00	227	3984	7945
B Skylights										
7 Wood &										
Metal		a b	 							
Doors		C								
B Above Grade V	/alls	а	PLUNKETT PLAC	DE WALL		2.86	1.17	3860	11040	4501
		b								
		С								
		d								
		е								
Partition Walls		f								
		g				+				
Below Grade W	alls	a				-				1
0 Coilings		b	19A 0 Cailing D-1	ou loiete D 40 loculation		4.70	0.73	1761	3091	1284
0 Ceilings		a b	10A-0 Ceiling Bel	ow Joists, R-49 Insulation		1.76	0.73	1761	3091	1284
		С	 						 	
Partition Ceilin	as	d	 							
. a. tition ouilli	5-	e	1			1				
1 Passive Floors		а								
		b								
Exposed Floor	5	С								<u> </u>
Slab (Perimete		d								
Basement Floo		е								
Partition Floor	-	f								
	T == · ·	g	<u> </u>			1			 	
2 Infiltration	Envelope Lea		Tight	Heated & Cooled	2077	Above Grade	e = Cu. Ft.	18693	2450	411
	No. of Firep	iaces	<u> </u>	Floor Area = Sq. Ft.	F		00	•		4000
3 Internal Gains			Appliance - 1200 l	Number of Bedrooms	5		Occupants	6	1	1380 1200
4 Sub Totals			, ppnance - 1200 i	51011					21828	17990
			7F-Ducts in Cond	litioned Space					2.020	.,,,,,,
5 Duct Loss & G	ain			eakage Class .12/.24		4			1	
				are Feet of Surface or Default = 1	Supply	1 4	Return	1	1	
6 Ventilation	Combustion Ai	r From (Conditioned Space		Heater	No	ne		1	
9 Blower Heat G				erformance data has no blower heat disc						1707
Total Sensible	Loss or Gain								21828	19697
						Latent Infiltratio	n load for coolir	ng		458
	1	BADAL	Y ENGINEERING	i		Latent load for o				1200
		2 WI	LSON PLACE			Latent load for	Small	Medium	Large	
	M		VERNON, NY 105	50	21	plants				
			4) 465-9010				duct in uncondit			
		h	padaly.com			Latent ventilation	n load for cooli	na		<u> </u>
		~	, ,			Total Latent G		-9		1658

SECOND FLOOR HEAT LOSS

		1113 to 12 COAE	- COMMUNICATOR INC.			
Project	SECOND FLOOR			ment Sensible Heat Ratio	0.75	ACCA
110,000	CEGGINE I EGGIN		Manual Overi	de Entry for Design CFM		Manual D
	Room Name	HEAT LOSS	HTG CFM	HEAT GAIN	CLG CFM	CFM
M	IASTER BEDROOM	4302	197	4735	263	263
M.A	ASTER BATHROOM	1881	86	1318	73	86
RE	EADING AREA / WIC	2232	102	2117	118	118
	BEDROOM 3	2874	132	2313	129	132
	BATHROOM 3	1242	57	658	37	57
	BATHROOM 2	670	31	568	32	32
	BEDROOM 2	2432	111	1306	73	111
	BEDROOM 1	2830	130	1939	108	130
ENT	TERTAINMENT AREA	2820	129	1981	110	129
	FOYER	544	25	1053	59	59
Ro	oom Envelope Totals	21828	1000	17990	1000	
	-		-	-		
Total Area	Construction Components	HEAT L	oss	HEAT GA	AIN .	
299	Windows & Glass Doors	5247	24.04%	9214	46.78%	1
	Skylights					1
	Wood & Metal Doors					1
3860	Above Grade Walls	11040	50.58%	4501	22.85%	
	Partition Walls					
	Below Grade Walls					
1761	Ceilings	3091	14.16%	1284	6.52%	1
	Partition Ceilings					1
	Passive Floors					1
	Exposed Floors					
	Slab Floors			•		
	Basement Floors					
	Partition Floors					
	Infiltration	2450	11.23%	411	2.09%	
	Internal Gains			2580	13.10%	
	Duct Loss & Gain					
	Ventilation					
	Blower Heat Gain			1707	8.67%	
	Total Sensible	21828	100.00%	19697	100.00%	
	Total Latent			1658		
	Total Cooling Load			21354		
	i otai ocoiiiig Load			21007		

BASEMENT AND FIRST FLOOR MANUAL D SUMMARY

	Air Conditioning Contractors of America, Manual D, Third Edition ACCA Manual D, 3rd Edition (D3) Residential Duct Systems, 2009 - 2016 (Worksheet 1)																																					
									Α	CC	Ά	Ma	an	ua	ıl I	D,	3r	d E	Ξd	iti	on	(D)3)	- Ro	esio	dentia	I D	uct Systems	s, 2009 - 2	2016	6 (Workshe	eet 1	l)				
																,	Su					Rι	un	ou	ts								Ed	quivile	nt l	Rect. D	uct	Equivilent
ID		Ro			_			ŀ	I-B	tuł	<u>1</u>			C-l	Btı	uh		ŀ	Itg	C	fm	1	Cló	g C	Cfm	D:	sn Cfn	n	Round Size	Velocity	/ F	Final Size	Н	leight		Wid	th	Flex
SR-1	В	ASE	ME	NT	1				30	50				7	'28	8			1	03	3			48	}		103		6	527		6						7
SR-2	В	ASE			2			_	30		_				28					03				48			103		6	527		6						7
SR-3		DIN								49				16						69				11(110		7	411		7						7
SR-4		DIN			_					49				16	78	3.5			(69			•	11(0		110		7	411		7						7
SR-5		KITO	HE	N	1			1	78	1.5	5			164	42	2.5			(60			•	108	8		108		7	402		7						7
SR-6		KITO	HE	N.	2			1	78	1.5	5			164	42	2.5			(60				108	8		108		7	402		7						7
SR-7		FC	YE	R					20	60				8	55	9				70				56)		70		6	356		6						6
SR-8		FAI	ИL	Y 1					15	62				14:	52	2.7			ţ	53				95	5		95		6	485		6						7
SR-9		FAI	ИL	Y 2	<u> </u>				15	62				14:	52	2.7			ļ	53				95	;		95		6	485		6						7
SR-10		FAI	ИL	Y 3	}				15	62				14:	52	2.7			ţ	53				95	5		95		6	485		6						7
SR-11		MU	ID I	RM			Ĺ		18	63				1(01	4		Ĺ	(63				66)		66		6	338		6			$_ extstyle e$			6
SR-12		BA	۱T۲	1			Ĺ		55	53				2	88	ô ¯				19				19)		19		4	215		4						4
SR-13			۱T۲				Ĺ		12	64				5	4′	1			-	43				35			43		5	314		5						5
SR-14		GUE	ST	RI	N		Ĺ		10	72				5	86	ô		Ĺ	,	36				38	}		38		5	281		5			$_ extstyle e$			5
SR-15		OF	FIC	Œ					26	15				18	84	8			(89			•	12 <i>′</i>	1		121		7	453		7						7
SR-16		Н	ΑL	L					10	43				4	34	4			,	35				28	3		35		4	405		4						5
SR-17		LIV	INC	3 1				1	39	4.5	5			1	18	6				47				78			78		6	396		6						6
SR-18		LIV	INC	3 2				1	39	4.5	5			1	18	6			4	47				78	3		78		6	396		6						6
SR-19																																						
SR-20																		T																				
							T	3	317	706	3		2	203	390	6.1		T	10	07	5		1	33	5		1475											
																	Sı	ıpp	oly	- S	ide	: Tı	rui	nk	S			•					Ed	quivile	nt l	Rect. D	uct	Equivilent
ID								As	SSO		_	_		ply	_	_		Ι.	_		l	T				n	sn Cfn	,	Da d C!==	V-1!4	Ι.	Final Cina	ш	la i a b t		Widt	414	Flex
1 1	1	2 3	: T	1	5	6	7	7	8	9	1 1	0	11	l 12	' '	13 I	14	1 1	5	16	1 17	7 1	18	19	20	יט ק	SII CII	"	Round Size	Velocity	/ ¹	Final Size	п	leight		vviu	tri	1
ST-1	1	2 3	1	1	5	6	7 1	, 	8	9	1 1	0	11	12 	1	13	14		5	16		7 1 	18	19	20	ָט ו		+			<u> </u>		П					
ST-1 ST-2	1	2 3	,	1	5 *	6 •/	, 	, 	8	9		0	11	12		13	14		5	16		7 1 	18	19	20	יט	215		8	616	/ ¹	8		6		8		9
ST-2	1	2 3	, ,	,	5	6 4	7		8	9			11	12		13	14		5	16	1,	1	18	19	20		215 577	" 	8 12	616 736	/ '	8 12		6		8 14	ļ	9 14
ST-2 ST-3	1	2 3	, ,	,	5 4 4 4	4	, ,	,	*		ļ	/	11	12		13	14	1:	5 •	16	17	7 1	18	19	20		215 577 854		8 12 14	616 736 799	/	8 12 14		6 8 8		8 14 19	ļ.)	9 14 16
ST-2 ST-3 ST-4	1	2 3	, ,	,	7 7 7	4	ļ	,	4 4	>	ļ	/					14	1:	5 ✓	16 	7	7 1	18	19	20		215 577		8 12	616 736	/ '	8 12		6		8 14	ļ.)	9 14
ST-2 ST-3 ST-4 ST-5	1	2 3	, ,	,	7 7 7	4	ļ	,	4 4	>	ļ	/					14	1:	<i>y</i>	16 -	7 7	, 1	18 •	19	20		215 577 854		8 12 14	616 736 799	/	8 12 14		6 8 8		8 14 19	ļ.)	9 14 16
ST-2 ST-3 ST-4 ST-5 ST-6	1	2 3	, ,	,	7 7 7	4	ļ	,	4 4	>	ļ	/					14		<i>y</i>	16	17	1	18	19	20		215 577 854		8 12 14	616 736 799	/ I	8 12 14		6 8 8		8 14 19	ļ.)	9 14 16
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7	1	2 3	, ,	,	7 7 7	4	ļ	,	4 4	>	ļ	/					14		<i>y</i>	16 •	17	7 1	√ 	19	20		215 577 854		8 12 14	616 736 799	/	8 12 14		6 8 8		8 14 19	ļ.)	9 14 16
ST-2 ST-3 ST-4 ST-5 ST-6	1	2 3	, ,	,	7 7 7	4	ļ	,	4 4	>	ļ	/				7	4		,	7	7 7	7 1	7				215 577 854		8 12 14	616 736 799	/	8 12 14		6 8 8 10	ent I	8 14 19 25)	9 14 16 18
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7	1	2 3		,	7 7 7	4	ļ	,	7 7 7	7 7		,	4			7	, , Re		,	7	7 7		7				215 577 854		8 12 14	616 736 799		8 12 14	Ec	6 8 8 10	nt I	8 14 19) j	9 14 16 18
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8	1	2 3		,	7 7 7	4	ļ	,	7 7 7	7 7		,	4	4		7	, , Re		,	7	7 7		7				215 577 854 1287		8 12 14 16	616 736 799 922		8 12 14 18	Ec	6 8 8 10	nt I	8 14 19 25) j	9 14 16 18 Equivilent
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8	1	2 3		,	7 7 7	4	ļ	,	7 7 7	7 7		,	4	4		7	, , Re		,	7	7 7		7				215 577 854 1287		8 12 14 16	616 736 799 922		8 12 14 18	Ec	6 8 8 10	ent I	8 14 19 25) j	9 14 16 18 Equivilent
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8		2 3		,	7 7 7	4	ļ	,	7 7 7	7 7		,	4	4		7	, , Re		,	7	7 7		7				215 577 854 1287		8 12 14 16	616 736 799 922		8 12 14 18	Ec	6 8 8 10	ent I	8 14 19 25) j	9 14 16 18 Equivilent
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8		2 3		,	7 7 7	4	ļ	,	7 7 7	7 7		,	4	4		7	, , Re		,	7	7 7		7				215 577 854 1287		8 12 14 16	616 736 799 922		8 12 14 18	Ec	6 8 8 10	ent I	8 14 19 25) j	9 14 16 18 Equivilent
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8 ID RR-1 RR-2 RR-3		2 3		,	7 7 7	4	ļ	,	7 7 7	7 7		,	4	4		7	, , Re		,	7	7 7		7				215 577 854 1287		8 12 14 16	616 736 799 922		8 12 14 18	Ec	6 8 8 10	ent I	8 14 19 25) j	9 14 16 18 Equivilent
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8 ID RR-1 RR-2 RR-3 RR-4		2 3		,	7 7 7	4	ļ	,	7 7 7	7 7		,	4	4		7	, , Re		,	7	7 7		7				215 577 854 1287		8 12 14 16	616 736 799 922		8 12 14 18	Ec	6 8 8 10	ent I	8 14 19 25) j	9 14 16 18 Equivilent
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8 ID RR-1 RR-2 RR-3 RR-4 RR-5		2 3		,	7 7 7	4	ļ	,	7 7 7	7 7		,	4	4		7	, , Re		,	7	7 7		7				215 577 854 1287		8 12 14 16	616 736 799 922		8 12 14 18	Ec	6 8 8 10	ent I	8 14 19 25) j	9 14 16 18 Equivilent
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8 ID RR-1 RR-2 RR-3 RR-4 RR-5 RR-6		2 3		,	7 7 7	4	ļ	,	7 7 7	7 7		,	4	4		7	, , Re		,	7	7 7		7				215 577 854 1287		8 12 14 16	616 736 799 922		8 12 14 18	Ec	6 8 8 10	ent I	8 14 19 25) j	9 14 16 18 Equivilent
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8 ID RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7		2 3		,	7 7 7	4	ļ	,	7 7 7	7 7		,	4	4		7	, , Re		,	7	7 7		7				215 577 854 1287		8 12 14 16	616 736 799 922		8 12 14 18	Ec	6 8 8 10	ent I	8 14 19 25) j	9 14 16 18 Equivilent
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8 ID RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7 RR-8		2 3		,	7 7 7	4	ļ	,	7 7 7	7 7		,	4	4		7	, , Re		,	7	7 7		7				215 577 854 1287		8 12 14 16	616 736 799 922		8 12 14 18	Ec	6 8 8 10	ent I	8 14 19 25) j	9 14 16 18 Equivilent
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8 ID RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7 RR-8 RR-9		2 3		,	7 7 7	4	ļ	,	7 7 7	7 7		,	4	4		7	Re		rn-	sie	de		Junco	out	ts_		215 577 854 1287		8 12 14 16	616 736 799 922		8 12 14 18	Ecc H	6 8 8 10 quiviler leight		8 14 19 25 Rect. D Widt	Puct th	9 14 16 18 Equivilent Flex
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8 ID RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7 RR-8 RR-9		2 3		,	7 7 7	4	ļ	As	SSO	ocia	ited	d S	- J	4	RI	uns	Re		rn-	sie	de	Ru	Junco	out	ts_	D:	215 577 854 1287	n	8 12 14 16	616 736 799 922	, !	8 12 14 18	Ec	6 8 8 10 quiviler leight		8 14 19 25	ouct th	9 14 16 18 Equivilent
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8 ID RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7 RR-8 RR-9 RR-10		2 3		,	7 7 7	4	ļ	As	SSO	ocia	ited	d S	- J	ply	RI	uns	Re		rn-	sie	de	Ru	Junco	out	ts_	De	215 577 854 1287	n	8 12 14 16 Round Size	616 736 799 922 Velocity	, !	8 12 14 18 Final Size	Ec	6 8 8 10 quivilei leight		8 14 19 25 Rect. D Widt	ouct th	9 14 16 18 Equivilent Flex
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8 ID RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7 RR-8 RR-9 RR-10				,	7 7 7	4	ļ	As	SSO	ocia	ited	d S	- J	ply	RI	uns	Re		rn-	sie	de	Ru	Junco	out	ts_	De	215 577 854 1287	n	8 12 14 16 Round Size	616 736 799 922 Velocity	, !	8 12 14 18 Final Size	Ec	6 8 8 10 quiviler leight		8 14 19 25 Widt	ouct th	9 14 16 18 Equivilent Flex Equivilent Flex
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8 ID RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7 RR-8 RR-9 RR-10 ID RT-1				,	7 7 7	4	ļ	As	SSO	ocia	ited	d S	- J	ply	RI	uns	Re		rn-	sie	de	Ru	Junco	out	ts_	De	215 577 854 1287	n	8 12 14 16 Round Size	616 736 799 922 Velocity	, !	8 12 14 18 Final Size	Ec	6 8 8 10 quiviler leight		8 14 19 25 Widt	ouct th	9 14 16 18 Equivilent Flex Equivilent Flex
ST-2 ST-3 ST-4 ST-5 ST-6 ST-7 ST-8 ID RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7 RR-8 RR-9 RR-10 ID RT-1 RT-2				,	7 7 7	4	ļ	As	SSO	ocia	ited	d S	- J	ply	RI	uns	Re		rn-	sie	de	Ru	Junco	out	ts_	De	215 577 854 1287	n	8 12 14 16 Round Size	616 736 799 922 Velocity	, !	8 12 14 18 Final Size	Ec	6 8 8 10 quiviler leight		8 14 19 25 Widt	ouct th	9 14 16 18 Equivilent Flex Equivilent Flex

SECOND FLOOR MANUAL D SUMMARY

													Ĩ								uts			Ouct Systems	,	,		Rect. Duct	Equivilent
ID		Ro	om	ID			·	I-Bt	uh			C-I	3tu		up	_			_		Cfn	ηT	Dsn Cfm	Round Size	Velocity	Final Size	Height	Width	Flex
SR-1	M	ASTE			M 1	1		075					3.7				53		Ť	_	38	Ť	88	6	448	6			6
SR-2	_	ASTE				_		075					3.7				53				38	T	88	6	448	6		1	6
SR-3		ASTE						075					3.7				53				38		88	6	448	6			6
SR-4	M	ASTE	RI	BDR	Μ	4	1	075	5.5		•	18	3.7	7 5			53	}		8	38		88	6	448	6			6
SR-5	N	/IAS	ER	ВА	TH			188	31			13	318	}			93	}		Ć	98		98	6	498	6			6
SR-6	R	EAD	ING	AR	EΑ	ı		111	16			10:	58.	5			55	<u>,</u>			79		79	6	400	6			6
SR-7			WI(_	111					58.				55				79		79	6	400	6			6
SR-8	_	BED						287					313	}			142				72	_	172	7	643	7			8
SR-9	+	BATH						124					58				61				19	_	61	5	449	5			5
SR-10	+	BATE						67					68		4		33				12	4	42	5	309	5			5
SR-11						_		121					53				60		1		18	4	60	5	439	5			5
SR-12	_	EDR				_		121					53		4		60		\bot		18	4	60	5	439	5			5
SR-13	_	EDR				_		141					9.5		4		70		\bot		72	4	72	5	528	5			6
SR-14	_	EDR				_	_	141					9.5		4		70		\bot		72	4	72	5	528	5			6
SR-15	_					_		141					0.5		4		69		\bot		74	4	74	5	539	5			6
SR-16	ΕN				:NI	2		141					0.5		4		69		+		74	4	74	5	539	5		ļ	6
SR-17		F	IYC	:K		+		54	4			1()53	5	4		27		+	7	78	4	78	6	398	6			6
SR-18																			1			4							
SR-19																						_							
SR-20															4							4							
								218	27			17	98				107				335		1370						1
														(Sup	pl	y-s	ide) Tı	run	ks						Equivilent	Rect. Duct	Equivilen
ID	1	2	3	4	5	6	7 A	8	ciat 9	ed 3	Sup 11		Rui 13	_	14	15	16	17	7 1	8	19 2	20	Dsn Cfm	Round Size	Velocity	Final Size	Height	Width	Flex
ST-1	4	4	4	J .	/	J				П			Г	T			Г	Ī	1				528	12	672	12	8	14	12
ST-2	4	4	>	,	1	4	4							m II				7	<u>/ </u>				684	12	872	14	8	19	14
ST-3	4	4	4	<i>y</i>	/	J	,	4	4	4	>	>	4	1	4	4	4	7	7				1335	16	957	18	10	25	18
ST-4				┸	Щ	┸		\perp					L	Щ			L	Ш	Щ	Щ	Щ								
ST-5		\Box		┸	┸	╝					Ш		L	Щ			L	╨	Щ	Щ	Щ								
ST-6	L	Щ	Щ	╨	4	4	Щ	Щ		Ш	Ц	\perp	L	Щ	┙		L	Щ	Щ	Щ	Щ	┙							
ST-7	Щ	Щ	Щ	╨	4	4	Щ	_		Ш	Ц	ot	L	Щ	┙		Щ	Щ.	Щ	Щ	4	┙							
ST-8	Щ	Ш	Щ	Щ	Щ	Щ	Щ	Щ		Ш			L	Щ			Ш	Ш	Щ	Щ	Щ								
<u> </u>															Ret	urn	1-si	de	Ru	ıno	uts	_						Rect. Duct	Equivilen
							A	sso	ciat	ed :	Sup	ply	Ru	ns	_							4	Dsn Cfm	Round Size	Velocity	Final Size	Height	Width	Flex
ID	-		ш	4	#	4	4	4	Ц	Ц	┙	L	╙	Щ	4		L	╨	#	4	4	4							
ID RR-1		Щ	-	Ш		#	4	4	Ц	Ц	\vdash	\vdash	╙	4	4	\vdash	#	#	#	4	#	4							
ID RR-1 RR-2	E	Н	#		7					ıl	II I	II.	ш	Ш			Ш	П	Ш	- 11	- 11								
ID RR-1 RR-2 RR-3				#	\prod	╬	4	-#	-	\vdash		_	₩	4٢	Γ		_	┿	-	┉	_	\neg							1
ID RR-1 RR-2 RR-3 RR-4						#	╣	╣	\Box	Ц			╙	#				#	#	#	#	4							1
ID RR-1 RR-2 RR-3 RR-4 RR-5						#															\exists								
ID RR-1 RR-2 RR-3 RR-4 RR-5 RR-6																													
ID RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7						#																							
RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7 RR-8						#																							
ID RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7 RR-8 RR-9																													
RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7 RR-8																													
RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7 RR-8 RR-9 RR-10															Ret	tur	n-s	ide	Tr	run	ks							Rect. Duct	
ID RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7 RR-8 RR-9 RR-10							A	ssoc	ciat	ed	Sup	oly	Ru		Ret	turi	n-s	ide	Tr	run	ks		Dsn Cfm	Round Size	Velocity	Final Size	Height	Width	Flex
RR-1 RR-2 RR-3 RR-4 RR-5 RR-6 RR-7 RR-8 RR-9 RR-10						-	A	ssoo	ciat	ed	Sup	oly	Ru		Ret	tur	n-s	ide	Tr	run	ks		Dsn Cfm 528 807	Round Size 12 14	Velocity 672 755	Final Size 12 14			Equivilen Flex 12

	В	A		L	Y
Ī	ENGINEER	ING DESIGN	<u>\:</u>		

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM

Peter Klein , associates, inc ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT 44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

ISSU	JES:	
#	DATE	DESCRIPTION
REV	<u> (ISIONS:</u>	
#	DATE	DESCRIPTION
		·

NEW SINGLE FAMILY RESIDENCE:


1A PLUNKETT PL WESTPORT, CT 10708

HEAT LOSS CALCULATIONS AND MANUAL D

CHECKED BY:

M-202.00

SHEET NO.: 26 OF 36




NAVIEN NPE-240A2 TANKLESS WATER HEATER

NPE-2 Series

Mavien


NPE-A2 and NPE-S2 Condensing Tankless Water Heaters





LOCHINVAR LOCKTEMP SJS060 STORAGE TANK





(8/22 Wesite update) ASB-500-5/21-Printed in U.S.A.

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550 ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY O UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R./ WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209. document may not be distributed, reproduce COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN AN WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID. CONSULTANT DE LA PUENTE ARC-CONSULTANT, LLC PATRICIA DE LA PUENTE CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM Peter Klein , associates, in ARCHITECTS - BUILDERS - DEVELOPER CONSTRUCTION MANAGEMENT 44 WINDING WOOD ROAD RYE BROOK , NEW YORK 10573 # DATE DESCRIPTION # DATE DESCRIPTION PROJECT TITLE:

NEW SINGLE FAMILY RESIDENCE:

<u>1A PLUNKETT PL</u> WESTPORT, CT 10708

DRAWING TITLE:

<u>SPECIFICATIONS</u>

SEAL AND SIGNATURE: AS NOTED 02/13/23 JOB NO.: 22335 DRAWN BY CHECKED BY

DRAWING NO.:

FOUNDATION & CONCRETE NOTES

F.1 NO BACK FILLING SHALL BE DONE UNTIL THE FOUNDATION WALLS HAVE BEEN BRACED AND WATERPROOFING HAS BEEN APPLIED.

F.2 ALL FOOTINGS ARE TO BE CARRIED DOWN TO A MINIMUM OF 3'-6" BELOW ADJACENT FINISHED GROUND LEVEL WHEN EXPOSED TO FROST, BELOW HOUSE DRAINS AND DOWN TO VIRGIN SOIL.

F.3 WHEN EXCAVATIONS ARE 5'-0" OR GREATER IN DEPTH FROM THE LEVEL OF ADJACENT GROUND, THE SIDES SHALL BE SHORED.

F.4 PROVIDE GUARD RAILS OR A FENCE AT EXCAVATIONS.

F.5 EXCAVATIONS SHALL BE SUBSTANTIALLY KEPT FREE OF WATER DURING FOUNDATION CONSTRUCTION.

F.6 ALL CONCRETE USED ON THIS PROJECT TO BE PROPORTIONED ON THE BASIS OF CALCULATED STRESSES LESS THAN 70% OF BASIC ALLOWABLE VALUES.

F.7 CONCRETE MATERIALS, DESIGN, AND CONSTRUCTION SHALL MEET THE REQUIREMENTS OF THE NYC BUILDING CODE & ACI STANDARD.

F.8 CONCRETE IS TO BE PROVIDED ON THE BASIS OF A PREQUALIFIED OR PREVIOUSLY ACCEPTED MIX. THE CONCRETE MIX IS TO EXHIBIT A STRENGTH AT LEAST 25% HIGHER THAN THE SPECIFIED VALUE. QUALITY CONTROL OF CONCRETE IS TO BE PROVIDED AT THE BATCH PLANT. THE RESULTS OF QUALITY CONTROL AND INSPECTION ARE TO APPEAR ON THE TICKET ACCOMPANYING EACH LOAD OF CONCRETE.

F.9 CONCRETE WHICH IN ITS FINAL STATE WILL BE EXPOSED TO THE ACTION OF FREEZING WEATHER AND ALL CONCRETE FOR GARAGE, FLOORS, ENTRANCE, PLATFORMS, STEPS AND PORCH FLOORS, RETAINING WALLS, SHALL HAVE MIX DESIGN WITH THE ENTRAINED AIR TO PROVIDE A CONCRETE WITH A MAXIMUM RESISTANCE TO FREEZING AND THAWING WEAR FOR THE AGGREGATE AND CEMENT USED.

F.10 CELLAR FLOOR SLAB SHALL BE MINIMUM 4" CONCRETE SLAB (NATURAL AGGREGATE CONCRETE CONFORMING TO ASTM A-33 WITH A MINIMUM 28 DAY STRENGTH OF 4,000 P.S.I.) PLACED ON 4" MINIMUM WELL COMPACTED GRAVEL OF CRUSHED STONE FILL AND REINFORCED WITH 6x6 W1.4XW1.4 WELDED WIRE FABRIC PLACED 1" BELOW TOP OF SLAB. PROVIDE VAPOR BARRIER BELOW SLAB ON GRADE.

F.11 SLABS ON GROUND SHALL BE POURED IN ALTERNATE PANELS OF 600 S.F. MAXIMUM IN AREA AND IN A CHECKERBOARD FASHION TO MINIMIZE SHRINKAGE. BACKFILL AT PIERS AND OVER FOOTINGS SHALL BE COMPACTED THOROUGHLY.

F.12 CONCRETE TO DEVELOP A MINIMUM STRENGTH OF 4,000 PSI AT 28 DAYS.

F.13 GARAGE SLAB AND CONCRETE EXPOSED TO WEATHER SHALL BE 4,000 PSI AT 28 DAYS.

F.14 ALL CONCRETE SLAB SHALL BE MINIMUM 4" THICK, AND SHALL BE REINFORCED WITH 6X6 W1.4 X W1.4 WWF.

F.15 REINFORCEMENT BARS SHALL BE FY=60,000 PSI & CONFORM TO ASTM A615, LATEST EDITION.

F.16 FOUNDATION WALLS AND FOOTINGS TO REST UPON 3 TONS/SQ.FT OF VIRGIN SOIL, TO BE VERIFIED BY THE SPECIAL INSPECTOR AND/OR PROJECT ENGINEER AFTER EXCAVATION AND BEFORE FOOTINGS ARE PLACED.

F.17 UNLESS OTHERWISE NOTED, ALL CONCRETE FOOTINGS TO BE 12" THICK.

UNDERPINNING AND DEWATERING.

F.18 PLAIN CONC. TO HAVE A MIN. CEMENT FACTOR OF 5 BAGS PER CU. YD. CONC. MAX. 8-1/2 GAL WATER/BAG OF CEM. AND DEVELOP A STRENGTH OF 4,000 PSI WHEN TESTED. PROVIDE AT LEAST 3 TEST CYLINDERS FOR EACH DAY OF POURING TESTED.

F.19 WHERE MORE THAN 50 CU. YD. OF AVERAGE CONC. ARE PLACED IN ANY STRUCTURE, A P.E. SHALL SUPERVISE THE TESTING. WHERE STEEL WIRE MESH IS USED, CONC. MIX SHALL BE ONE PART CEMENT, TWO PARTS SAND AND FIVE PARTS COARSE AGGREGATE. WIRE MESH MIN. TENSILE STRENGTH 55,000 PSI

F.20 FOUNDATION WALLS BELOW GRADE TO BE WATERPROOFED WITH BITUMINOUS COATING OR EQUAL.

F.21 WHEN UNDERPINNING IS REQUIRED, NO WORK TO BE STARTED UNTIL SEPARATE APPLICATION OR AMENDMENT RELATING TO UNDERPINNING IS APPROVED.

F.22 FOOTING TO BE STEPPED AT A MAX. OF 30 DEGREE SLOPE SO AS NOT TO EXERT ANY LATERAL PRESSURE ON ADJACENT FOOTINGS OR FOUNDATION WALLS.

F.23 FOR EACH CLASS OF CONC. PLACED ON ANY ONE DAY 3 STANDARD ACCEPTANCE CYLINDERS SHALL BE MADE FOR TESTING.

F.24 THE GENERAL CONTRACTOR OR CONSTRUCTION MANAGER AND/OR THE FOUNDATION CONTRACTOR SHALL BE SOLELY AND FULLY RESPONSIBLE FOR ALL EXCAVATION WORK INCLUDING BUT NOT LIMITED TO THE DESIGN, INSTALLATION AND MAINTENANCE OF SHEETING AND SHORING, PROTECTION OF SLOPES,


F.25 THE GENERAL CONTRACTOR OR CONSTRUCTION MANAGER AND/OR THE FOUNDATION CONTRACTOR SHALL RETAIN A PROFESSIONAL ENGINEER REGISTERED IN THE STATE IN WHICH THE PROJECT IS LOCATED TO DESIGN ALL SHEETING AND SHORING, UNDERPINNING AND DEWATERING SYSTEMS.

F.26 THE SLOPE BETWEEN ADJACENT FOOTING BOTTOMS SHALL NOT EXCEED 1 VERTICAL TO 1 HORIZONTAL.

F.27 FOUNDATION WALLS AND/OR GRADE BEAMS SHALL BE CAST IN ALTERNATE PANELS NOT TO EXCEED 60 FEET IN LENGTH. CONSTRUCTION JOINTS SHALL BE PLACED AT POINTS OF MINIMUM SHEAR, GENERALLY AT MIDSPAN. ALLOW 7 DAYS MINIMUM BETWEEN ADJACENT POURS.

F.29 FOUNDATION WALLS AND/OR GRADE BEAMS, SHALL BE TEMPORARILY BRACED LATERALLY TO RESIST EARTH PRESSURE, WIND, CONSTRUCTION LOADS AND OTHER LATERAL LOADS UNTIL FRAMED SLABS AND SLABS ON GRADE THAT PERMANENTLY BRACE THESE WALLS AND/OR GRADE BEAMS HAVE BEEN IN PLACE 28 DAYS (MINIMUM).

F.30 TRUCKS, BULLDOZERS OR OTHER HEAVY EQUIPMENT SHALL NOT BE PERMITTED CLOSER THAN 8'-0" FROM ANY FOUNDATION WALL BEFORE THE COMPLETE STRUCTURAL FRAME IS IN PLACE.







GINEERING DESIGN:

LAW ARTICLE 145, SECTION 7209.

BADALY ENGINEERING PLLC

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED, COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN ANY WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION

OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PATRICIA DE LA PUENTE

PRINCIPAL
CEL. 914-6181847
PDLPARCHITECTURE@HOTMAIL.COM

PETER KLEIN, ASSOCIATES, INC ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

ISSUES:

DATE DESCRIPTION

REVISIONS:

DATE DESCRIPTION

NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TITLE:

FOUNDATION PLAN

SCALE:
AS NOTED


DATE:
02/13/23


DB NO.:
22335


DRAWN BY:
AK

CHECKED BY:

FO-100.00








REINFORCED CONCRETE BLOCK WALL Scale: 1/4" = 1'-0"


STANDARD HOOK

STANDARD HOOK

TYPICAL CMU WALL REINFORCEMENT DETAILS



- 1. ALL CONCRETE SHALL BE 3,500 PSI MINIMUM STONE CONCRETE WITH SUPERPLASTICIZER UNLESS OTHERWISE NOTED ELSEWHERE.
- 2. THE CONTRACTOR SHALL SUBMIT PROPOSED METHOD OF CURING AND APPROPRIATE CURING PRODUCT SPECIFICATIONS.
- 3. CURING OF CONCRETE IS TO START AS SOON AS FINISH WILL NOT BE MARRED THEREBY. IT WILL NOT BE PERMISSIBLE TO DELAY THE CURING UNTIL THE MORNING AFTER THE CONCRETE IS CAST.
- 4. THE CONTRACTOR SHALL SUBMIT A DRAWING FOR ARCHITECT'S REVIEW INDICATING THE SIZE AND LOCATION OF WELDED WERE FABRIC, THE DETAILS AND LOCATIONS OF SPLICES AND THE LOCATION OF ALL JOINTS (CONSTRUCTION AND.OR EXPANSION AND/OR CONTROL).



CONCRETE WALL & FOOTING CORNER & INTERSECTION DETAIL Scale: 1" = 1'-0"

STANDARD HOOK

<u>CORNER</u>

SLAB-ON-GRADE DETAIL

DIMENSIONS "Ld" AS NOTED ON DRAWINGS SHALL BE AS FOLLOWS:

BEAMS			COLUMNS	
BAR SIZE	BOTTOM BARS	TOP BARS	BAR SIZE	Ld
#3	15	19	#3	15
#4	19	25	#4	19
#5	24	31	#5	24
#6	29	37	#6	29
#7	42	54	#7	42
#8	48	62	#8	48
#9	54	70	#9	54
#10	60	78	#10	60
#11	66	85	#11	66

TABLE ASSUMPTIONS: CONCRETE f'c = 4 KSI

- REINFORCING BAR fy = 60 KSIA MINIMUM CLEAR COVER PROVIDED AS
- PER ACI 318 SECTION 7.7
- NORMAL WEIGHT CONCRETE MINIMUM BAR CLEAR SPACING SHALL SATISFY EITHER ≥ 2 X BAR DIAMETER OR ≥ 1 X BAR DIAMETER WITH ACI 318 CODE MINIMUM STIRRUPS OR TIES SO AS TO NOT QUALIFY AS 'OTHER CASES' IN ACI 318 SECTION 12.2.

WALLS			
BAR SIZE	VERTICAL BARS	HORIZONTAL BARS	
#3	15	19	
#4	19	25	
#5	24	31	
#6	29	37	
#7	42	54	
#8	48	62	
#9	54	70	
#10	60	78	
#11	66	85	

FOR: f'c = 3 KSI Ld = 1.15 x TABLE VALUE

f'c = 5 KSI Ld = 0.89 x TABLE VALUE

f'c = 6 KSI Ld = 0.82 x TABLE VALUE

f'c = 8 KSI Ld = 0.71 x TABLE VALUE

f'c = 4 KSI

Ld = 1.00 x TABLE VALUE

	WALLS			SLABS/	MATS	
BAR SIZE	VERTICAL BARS	HORIZONTAL BARS	BAR	THICKNESS 12" OR LESS		S GREA N 12'' ARS
#3	15	19	SIZE	A 1 1		
#4	19	25		ALL	BOTTOM	TO
#5	24	31		BARS	BARS	BAF
#6	29	37	#3	15	15	19
#7	42	54	#4	19	19	25
#8	48	62	#5	24	24	31
#9	54	70	#6	29	29	37
#10	60	78	#7	42	42	54
#11	66	85	#8	48	48	62
			#9	54	54	70
			#10	60	60	78
			#11	66	66	85

EATER

CLEAR COVER SHALL NOT BE LESS THAN BAR

DIAMETER FOR LAP SPLICES, MULTIPLY TABULATED VALUE

FOR LIGHT WEIGHT AGGREGATE CONCRETE, MULTIPLY THE TABULATED VALUES BY 1.3 FOR EPOXY COATED BARS, MULTIPLY THE


TABULATED VALUES BY 1.5 FOR BARS NOT MEETING CLEAR SPLACING REQUIREMENT AS INDICATED IN THE TABLE ASSUMPTIONS AND THEREFORE CONSIDERED 'OTHER CASES', MULTIPLY THE

TABULATED VALUE BY 1.5 COMBINATIONS OF EFFECTS DUE TO CONCRETE STRENGTH, CONCRETE WEIGHT, EPOXY BARS, AND BAR CLEAR SPACING ARE CUMULATIVE. 'Ld' SHALL BE MULTIPLIED BY **EACH FACTOR**

TO FIND THE CORRECT VALUE ACI DOES NOT PERMIT LAP SPLICES OF #14 OR #18 BARS. BARS OF THIS SIZE SHALL COUPLED BY ACCEPTABLE MECHANICAL MEANS


LENGTH TO FORM BEND OR HOOK

CAST MONOLITHICALLY



4 BAR DIA. #9-#11 INCLUSIVE -12 BAR DIA.

TYPICAL HOOK DETAILS



CAST SEPERATELY

SINGLE PIPE PENETRATION

STANDARD HOOK


DOWELS - SAME SIZE

AND SPACING AS

HORIZONTAL WALL REINFORCING

INTERSECTION

STANDARD HOOK



DOUBLE PIPE PENETRATION

RYE BROOK , NEW YORK 10573 # DATE DESCRIPTION # DATE

NGINEERING DESIGN:

914) 465-9010

BADALY ENGINEERING PLLC

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY C UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION LAW ARTICLE 145, SECTION 7209.

document may not be distributed, reproduce

COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN AN' WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM

BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION

CONSULTANT

DE LA PUENTE ARC-CONSULTANT, LLC

PATRICIA DE LA PUENTE

CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM

Peter Klein , associates, in

ARCHITECTS - BUILDERS - DEVELOPERS

CONSTRUCTION MANAGEMENT

44 WINDING WOOD ROAD

OF THIS DOCUMENT SHALL RENDER IT INVALID.

NEW SINGLE FAMILY RESIDENCE:

<u>1A PLUNKETT PL</u> WESTPORT, CT 10708

DESCRIPTION

DRAWING TITLE:

PROJECT TITLE:

CONC. & MASONRY <u>DETAILS</u>

SEAL AND SIGNATURE: AS NOTED 02/13/23 JOB NO.: 22335 DRAWN BY:


DRAWING NO .:

HECKED BY



STRUCTURAL PLAN NOTES:

- 1. ALL WOOD MEMBERS TO BE #2DF-L OR BETTER, UNLESS OTHERWISE NOTED
- 2. ALL WOOD JOISTS TO BE AT MAX 16" O.C. SPACING, UNLESS OTHERWISE NOTED





BADAL

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

914) 465-9010 any alterations of these plans, unless done by c UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION

LAW ARTICLE 145, SECTION 7209. DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCE COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN AN' WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATIO OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PETER KLEIN , ASSOCIATES, IN ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

CEL. 914-6181847

PDLPARCHITECTURE@HOTMAIL.COM

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

<u>ISS</u> L	JES:	
#	DATE	DESCRIPTION
RE\	/ISIONS:	
#	DATE	DESCRIPTION

NEW SINGLE FAMILY RESIDENCE:


<u>1A PLUNKETT PL</u> WESTPORT, CT 10708

DRAWING TITLE:

PROJECT TITLE:


FIRST FLOOR STRUCTURAL PLAN

AS NOTED 02/13/23 22335 DRAWN BY CHECKED BY



STRUCTURAL PLAN NOTES:

- 1. ALL WOOD MEMBERS TO BE #2DF-L OR BETTER, UNLESS OTHERWISE NOTED
- 2. ALL WOOD JOISTS TO BE AT MAX 16" O.C. SPACING, UNLESS OTHERWISE NOTED
- 3. ///// INDICATES PROPOSED 2X6 EXTERIOR BEARING WALL
- 4. REFER TO WINDOW SCHEDULE FOR HEADER SIZES IN EXTERIOR WALLS





BADAL

LAW ARTICLE 145, SECTION 7209.

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

any alterations of these plans, unless done by c UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION

COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN AN' WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATIO OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PATRICIA DE LA PUENTE CEL. 914-6181847
PDLPARCHITECTURE@HOTMAIL.COM

PETER KLEIN , ASSOCIATES, IN ARCHITECTS - BUILDERS - DEVELOPERS CONSTRUCTION MANAGEMENT

44 WINDING WOOD ROAD

RYE BROOK , NEW YORK 10573

<u>ISS</u> l	JES:	
#	DATE	DESCRIPTION
<u>RE\</u>	/ISIONS:	
#	DATE	DESCRIPTION

NEW SINGLE FAMILY RESIDENCE:


<u>1A PLUNKETT PL</u> WESTPORT, CT 10708

DRAWING TITLE:

PROJECT TITLE:


SECOND FLOOR STRUCTURAL PLAN

SEAL AND SIGNATURE: 02/13/23 DRAWN BY



STRUCTURAL PLAN NOTES:

- 1. ALL WOOD MEMBERS TO BE #2DF-L OR BETTER, UNLESS OTHERWISE NOTED
- 2. ALL WOOD JOISTS TO BE AT MAX 16" O.C. SPACING, UNLESS OTHERWISE NOTED
- 3. INDICATES PROPOSED 2X6 EXTERIOR BEARING WALL
- 4. REFER TO WINDOW SCHEDULE FOR HEADER SIZES IN EXTERIOR WALLS





BADALY

GINEERING DESIGN:

BADALY ENGINEERING PLLC 2 WILSON PLACE, MT. VERNON, NY 10550

ANY ALTERATIONS OF THESE PLANS, UNLESS DONE BY OR UNDER THE DIRECTION OF A NYS LICENSED P.E. (OR R.A. WHERE APPLICABLE) IS A VIOLATION OF THE NYS EDUCATION

LAW ARTICLE 145, SECTION 7209.

DOCUMENT MAY NOT BE DISTRIBUTED, REPRODUCED COPIED, PUBLISHED, TRANSMITTED, MODIFIED, OR IN AN' WAY EXPLOITED WITHOUT WRITTEN PERMISSION FROM BADALY ENGINEERING. ANY UNAUTHORIZED MODIFICATION OF THIS DOCUMENT SHALL RENDER IT INVALID.

CONSULTANT



PATRICIA DE LA PUENTE

PETER KLEIN, ASSOCIATES, INC
ARCHITECTS - BUILDERS - DEVELOPERS
CONSTRUCTION MANAGEMENT
44 WINDING WOOD ROAD

CEL. 914-6181847 PDLPARCHITECTURE@HOTMAIL.COM

RYE BROOK , NEW YORK 10573

ISSUES:
DATE DESCRIPTION

REVISIONS:
DATE DESCRIPTION

NEW SINGLE FAMILY RESIDENCE:

1A PLUNKETT PL WESTPORT, CT 10708

DRAWING TITLE:

ATTIC STRUCTURAL PLAN

SCALE:
AS NOTED

DATE:
02/13/23

JOB NO.:
22335

DRAWN BY:
AK



SEAL AND SIGNATURE:

S-103.00

